

# 屋内照明器具特性

品番 (品名)	LGB50920														
光源	LED5000_70_1670 x1 1670.0 lm														
管理番号	K0154732(0)DB1														
BZ分類	BZ6/0.7/BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	16%	室指数	照明率 ( X0.01 )																ZCM		
下方光束	84%																				
保守率	良 中 否	0.69	0.6	53	40	33	27	51	39	32	27	47	37	30	26	43	35	29	25	22	
		0.67	0.8	62	50	42	37	60	49	41	36	55	46	39	34	51	43	38	33	30	
			1.0	69	58	50	44	66	56	48	43	61	52	46	41	56	49	44	39	35	
		0.63	1.25	75	64	57	51	72	62	55	50	66	59	52	48	61	55	50	46	41	
下方投影面積	c m <sup>2</sup>	1.5	79	69	62	56	76	67	60	55	70	63	57	53	65	59	54	50	45		
		2.0	84	76	70	64	81	74	68	63	75	69	64	60	70	65	61	57	52		
取付高さ	器具間隔最大限		2.5	88	81	75	70	85	78	73	68	79	74	69	65	74	69	66	62	57	
	横方向 (A)	縦方向 (B)	3.0	90	84	79	74	87	82	77	73	81	77	73	69	76	72	69	66	60	
1.5m	2.07m	1.97m	4.0	94	89	84	80	91	86	82	78	85	81	78	75	79	76	73	71	65	
2	2.74	2.54	5.0	96	92	88	84	93	89	85	82	87	84	81	78	81	79	76	74	68	
2.5	3.41	3.13	7.0	98	95	92	89	95	92	89	87	89	87	85	83	84	82	80	78	72	
3	4.08	3.73	10.0	100	98	95	93	97	95	93	91	91	89	88	86	86	84	83	82	75	

