

屋内照明器具特性

品番 (品名)	L G B 5 1 9 1 3									
光源	LED5000_70_565 x1 565.0 lm									
管理番号	K0154844 (0) DB 1									
B Z 分類	B Z 1 0									

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %					1 0 %				1 0 %				1 0 %				0 %
上方光束 下方光束		4 9 % 5 1 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 9	0 . 6	4 2	2 9	2 1	1 5	3 8	2 7	1 9	1 4	3 1	2 2	1 6	1 1	2 4	1 7	1 2	8	3	
			0 . 6 7	0 . 8	5 0	3 7	2 8	2 2	4 6	3 4	2 6	2 0	3 7	2 8	2 1	1 6	2 9	2 2	1 7	1 3	6	
			0 . 6 3	1 . 0	5 6	4 4	3 4	2 8	5 1	4 0	3 2	2 5	4 1	3 3	2 6	2 1	3 3	2 6	2 0	1 6	8	
下方投影面積 等価発光面積		c m ² c m ²	1 . 2 5	6 2	5 0	4 1	3 4	5 6	4 5	3 7	3 1	4 6	3 7	3 1	2 5	3 6	3 0	2 4	2 0	1 1		
			1 . 5	6 6	5 5	4 6	3 9	6 0	5 0	4 2	3 6	4 9	4 1	3 5	3 0	3 9	3 3	2 8	2 4	1 4		
取付 高さ		器具間隔最大限 横方向 (A) 縦方向 (B)	2 . 0	7 2	6 2	5 4	4 7	6 6	5 7	4 9	4 3	5 4	4 7	4 1	3 6	4 3	3 8	3 3	2 9	1 8		
			2 . 5	7 6	6 7	5 9	5 3	6 9	6 1	5 5	4 9	5 7	5 1	4 6	4 1	4 6	4 1	3 7	3 3	2 1		
			3 . 0	7 8	7 0	6 3	5 7	7 2	6 5	5 9	5 3	6 0	5 4	4 9	4 5	4 8	4 4	4 0	3 7	2 4		
			1 . 5m 0 m 2 . 0 9 m	4 . 0	8 2	7 5	6 9	6 4	7 6	7 0	6 4	5 9	6 3	5 9	5 4	5 0	5 2	4 8	4 5	4 1	2 8	
			2 0 2 . 7 4	5 . 0	8 5	7 9	7 4	6 9	7 8	7 3	6 8	6 4	6 6	6 1	5 8	5 4	5 4	5 1	4 8	4 5	3 0	
			2 . 5 0 3 . 3 9	7 . 0	8 8	8 3	7 9	7 5	8 1	7 7	7 3	6 9	6 9	6 5	6 2	5 9	5 7	5 4	5 2	4 9	3 4	
			3 0 4 . 0 6	1 0 . 0	9 0	8 7	8 3	8 0	8 4	8 0	7 7	7 4	7 1	6 8	6 6	6 4	5 9	5 7	5 5	5 3	3 8	

