

屋内照明器具特性	
品番 (品名)	LGB54150K
光源	LDA7L-G-E17/Z60E/S/W/2 ×1 760.0 1m
管理番号	K0157124(0)DR1
BZ分類	BZ5/0.7/BZ4/2.8/BZ3

器具効率	50%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	50%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	2.8	2.2	1.8	1.5	2.7	2.2	1.8	1.5	2.6	2.1	1.8	1.5	2.5	2.1	1.7	1.5	1.4
	中	0.63	0.8	3.4	2.8	2.4	2.2	3.3	2.8	2.4	2.2	3.2	2.7	2.4	2.1	3.1	2.7	2.4	2.1	2.0
	否	0.56	1.0	3.8	3.3	2.9	2.6	3.7	3.2	2.9	2.6	3.5	3.1	2.8	2.6	3.4	3.1	2.8	2.6	2.5
			1.25	4.1	3.6	3.3	3.1	4.0	3.6	3.3	3.0	3.9	3.5	3.2	3.0	3.7	3.4	3.2	3.0	2.9
下方投影面積		cm ²	1.5	4.3	3.9	3.6	3.4	4.2	3.9	3.6	3.3	4.1	3.8	3.5	3.3	4.0	3.7	3.5	3.3	3.2
等価発光面積		cm ²	2.0	4.6	4.3	4.0	3.8	4.5	4.2	4.0	3.8	4.4	4.1	3.9	3.7	4.2	4.0	3.8	3.7	3.6
取付高さ	器具間隔最大限		2.5	4.7	4.5	4.3	4.1	4.7	4.4	4.2	4.0	4.5	4.3	4.1	4.0	4.4	4.2	4.1	3.9	3.8
	横方向 (A)	縦方向 (B)	3.0	4.9	4.6	4.4	4.3	4.8	4.6	4.4	4.2	4.7	4.5	4.3	4.2	4.5	4.4	4.2	4.1	4.0
Hm	1.87Hm	1.87Hm	4.0	5.0	4.8	4.7	4.5	4.9	4.8	4.6	4.5	4.8	4.7	4.5	4.4	4.7	4.6	4.5	4.4	4.2
			5.0	5.1	4.9	4.8	4.7	5.0	4.9	4.8	4.6	4.9	4.8	4.7	4.6	4.8	4.7	4.6	4.5	4.4
			7.0	5.2	5.1	5.0	4.9	5.1	5.0	4.9	4.8	5.0	4.9	4.8	4.7	4.9	4.8	4.7	4.7	4.5
			10.0	5.2	5.2	5.1	5.0	5.2	5.1	5.0	5.0	5.1	5.0	4.9	4.9	4.9	4.9	4.8	4.8	4.7

