

屋内照明器具特性	
品番 (品名)	LGB72774
光源	LED5000_70_780 x1 780.0 lm
管理番号	K0135851(0)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	1%	床	10%				10%				10%				10%				0%				
下方光束	99%	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	5.6	4.4	3.6	3.0	5.5	4.3	3.5	3.0	5.2	4.2	3.5	3.0	5.0	4.1	3.4	3.0	2.8			
	中	0.6	0.8	6.6	5.4	4.6	4.0	6.4	5.3	4.6	4.0	6.1	5.2	4.5	4.0	5.9	5.0	4.4	4.0	3.7			
	否	0.56	1.0	7.3	6.2	5.4	4.8	7.1	6.1	5.3	4.8	6.8	5.9	5.2	4.7	6.5	5.7	5.1	4.7	4.4			
			1.25	7.9	6.9	6.1	5.5	7.7	6.8	6.1	5.5	7.3	6.6	5.9	5.4	7.0	6.4	5.8	5.4	5.1			
下方投影面積	cm ²		1.5	8.3	7.4	6.7	6.1	8.1	7.3	6.6	6.1	7.8	7.0	6.5	6.0	7.4	6.8	6.3	5.9	5.7			
	等価発光面積		cm ²	2.0	8.8	8.1	7.5	6.9	8.7	8.0	7.4	6.9	8.3	7.7	7.2	6.8	8.0	7.5	7.1	6.7	6.4		
取付高さ	器具間隔最大限		2.5	9.2	8.5	8.0	7.5	9.0	8.4	7.9	7.5	8.7	8.2	7.7	7.3	8.4	8.0	7.6	7.2	7.0			
	横方向 (A)	縦方向 (B)	3.0	9.4	8.9	8.4	8.0	9.3	8.7	8.3	7.9	9.0	8.5	8.1	7.8	8.6	8.3	7.9	7.6	7.3			
Hm	1.28Hm	1.28Hm	4.0	9.8	9.3	8.9	8.5	9.6	9.2	8.8	8.5	9.3	8.9	8.6	8.3	9.0	8.7	8.4	8.2	7.9			
			5.0	10.0	9.6	9.2	8.9	9.8	9.5	9.1	8.8	9.5	9.2	8.9	8.7	9.2	9.0	8.7	8.5	8.2			
			7.0	10.2	9.9	9.6	9.4	10.0	9.8	9.5	9.3	9.7	9.5	9.3	9.1	9.5	9.3	9.1	8.9	8.6			
			10.0	10.4	10.2	10.0	9.8	10.2	10.0	9.8	9.7	9.9	9.8	9.6	9.5	9.7	9.5	9.4	9.3	9.0			

