

# 屋内照明器具特性

品番 (品名)	LGB71760	
光源	LED2700_70_385 ×1	385.0 1m
管理番号	K0138632(0)DB1	
BZ分類	BZ1	

器具効率	101%	天井	80%				70%				50%				30%				0%				
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
下方光束	101%	床		10%				10%				10%				10%				0%			
室指数	照明率 ( X0.01 )																			ZCM			
保守率	良 0.67	0.6	0.6	83	76	72	69	82	76	72	69	81	75	72	69	79	75	71	69	68			
	中 0.63		0.8	89	83	79	76	88	83	79	76	87	82	79	76	85	81	78	76	75			
	否 0.56		1.0	93	88	84	81	92	87	84	81	90	86	83	81	89	85	82	80	79			
下方投影面積	cm <sup>2</sup>	等価発光面積	cm <sup>2</sup>	1.25	96	91	88	85	95	91	88	85	93	90	87	84	91	88	86	84	83		
				1.5	98	94	91	88	97	93	90	88	95	92	89	87	93	91	89	87	85		
取付高さ	器具間隔最大限		Hm	0.42Hm	0.42Hm	2.5	103	100	97	95	101	99	97	95	99	97	95	94	97	96	94	93	91
	横方向 (A)	縦方向 (B)				3.0	104	101	99	97	103	100	98	97	100	99	97	95	98	97	96	94	92
Hm	0.42Hm	0.42Hm	4.0	105	103	101	100	104	102	101	99	102	100	99	98	100	99	97	96	94			
			5.0	106	104	103	102	105	103	102	101	103	101	100	99	100	99	99	98	95			
Hm	0.42Hm	0.42Hm	7.0	107	106	105	104	106	105	104	103	103	103	102	101	101	101	100	99	97			
			10.0	107	107	106	105	106	106	105	104	104	103	103	102	102	101	101	100	98			

