

# 屋内照明器具特性

|         |                             |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|-----------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | LGB76322                    |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED2700_70_750 x1 750.0 l m |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0148419 (0) DB 1           |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ4/3.5/BZ3                 |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                  |          |                  |      |      |      |      |      |      |      |      |      |      |     |     |     |     |     |     |     |
|--------|------------------|----------|------------------|------|------|------|------|------|------|------|------|------|------|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 100%             | 天井       | 80%              |      |      |      | 70%  |      |      |      | 50%  |      |      |     | 30% |     |     |     | 0%  |     |
|        |                  |          | 壁                | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 70   | 50   | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
| 上方光束   | 0%               | 反射率      | 10%              |      |      |      | 10%  |      |      |      | 10%  |      |      |     | 10% |     |     |     | 0%  |     |
| 下方光束   | 100%             |          | 床                | 10%  |      |      |      | 10%  |      |      |      | 10%  |      |     |     | 10% |     |     |     | 0%  |
|        |                  | 室指数      | 照明率 ( X0.01) ZCM |      |      |      |      |      |      |      |      |      |      |     |     |     |     |     |     |     |
| 保守率    | 良<br>中<br>否      | 0.67     | 0.6              | 5.9  | 4.7  | 4.0  | 3.5  | 5.8  | 4.7  | 4.0  | 3.5  | 5.5  | 4.6  | 3.9 | 3.4 | 5.3 | 4.5 | 3.9 | 3.4 | 3.2 |
|        |                  | 0.63     | 0.8              | 6.9  | 5.9  | 5.1  | 4.6  | 6.8  | 5.8  | 5.1  | 4.6  | 6.5  | 5.7  | 5.0 | 4.5 | 6.3 | 5.5 | 5.0 | 4.5 | 4.3 |
|        |                  |          | 1.0              | 7.6  | 6.6  | 5.9  | 5.4  | 7.5  | 6.5  | 5.9  | 5.4  | 7.2  | 6.4  | 5.8 | 5.3 | 6.9 | 6.2 | 5.7 | 5.3 | 5.1 |
|        |                  | 0.56     | 1.25             | 8.2  | 7.3  | 6.7  | 6.2  | 8.1  | 7.3  | 6.6  | 6.1  | 7.8  | 7.1  | 6.5 | 6.1 | 7.5 | 6.9 | 6.4 | 6.1 | 5.8 |
| 下方投影面積 | c m <sup>2</sup> | 1.5      | 8.6              | 7.8  | 7.2  | 6.7  | 8.5  | 7.8  | 7.2  | 6.7  | 8.2  | 7.6  | 7.1  | 6.7 | 7.9 | 7.4 | 7.0 | 6.6 | 6.4 |     |
|        |                  | 2.0      | 9.2              | 8.5  | 8.0  | 7.6  | 9.0  | 8.4  | 8.0  | 7.5  | 8.8  | 8.3  | 7.8  | 7.5 | 8.5 | 8.1 | 7.7 | 7.4 | 7.2 |     |
| 取付高さ   | 器具間隔最大限          |          | 2.5              | 9.5  | 9.0  | 8.5  | 8.1  | 9.4  | 8.9  | 8.5  | 8.1  | 9.1  | 8.7  | 8.3 | 8.0 | 8.8 | 8.5 | 8.2 | 7.9 | 7.7 |
|        | 横方向 (A)          | 縦方向 (B)  | 3.0              | 9.7  | 9.3  | 8.9  | 8.5  | 9.6  | 9.2  | 8.8  | 8.5  | 9.3  | 9.0  | 8.7 | 8.4 | 9.1 | 8.8 | 8.5 | 8.3 | 8.0 |
| H m    | 1.21 H m         | 1.21 H m | 4.0              | 10.0 | 9.7  | 9.3  | 9.1  | 9.9  | 9.5  | 9.3  | 9.0  | 9.6  | 9.3  | 9.1 | 8.9 | 9.4 | 9.1 | 8.9 | 8.7 | 8.5 |
|        |                  |          | 5.0              | 10.2 | 9.9  | 9.6  | 9.4  | 10.0 | 9.8  | 9.5  | 9.3  | 9.8  | 9.6  | 9.4 | 9.2 | 9.5 | 9.4 | 9.2 | 9.0 | 8.8 |
|        |                  |          | 7.0              | 10.4 | 10.1 | 10.0 | 9.8  | 10.2 | 10.0 | 9.9  | 9.7  | 10.0 | 9.8  | 9.7 | 9.5 | 9.7 | 9.6 | 9.5 | 9.4 | 9.1 |
|        |                  |          | 10.0             | 10.5 | 10.3 | 10.2 | 10.1 | 10.4 | 10.2 | 10.1 | 10.0 | 10.1 | 10.0 | 9.9 | 9.8 | 9.9 | 9.8 | 9.7 | 9.6 | 9.3 |

