

屋内照明器具特性

品番 (品名) **LGB76472**

光源 LED2700_70_690 ×1 690.0 1m

管理番号 K0151663(0)DB1

BZ分類 BZ1/0.7/BZ2

器具効率	100%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	100%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	72	63	57	53	71	62	57	53	69	62	57	53	67	61	56	53	52	
	中 0.63	0.8	80	72	66	62	79	71	66	62	76	70	65	62	75	69	65	62	60	
	否 0.56	1.0	85	78	72	68	84	77	72	68	81	76	71	68	79	74	71	67	66	
下方投影面積 等価発光面積	cm ²	1.25	89	83	78	74	88	82	78	74	86	81	77	73	84	79	76	73	71	
		1.5	92	87	82	79	91	86	82	78	89	84	81	78	87	83	80	77	75	
		2.0	96	92	88	85	95	91	87	84	93	89	86	83	90	87	85	82	80	
取付高さ	器具間隔最大限		2.5	99	95	91	88	97	94	91	88	95	92	89	87	93	90	88	84	
	横方向 (A)	縦方向 (B)	3.0	100	97	94	91	99	96	93	91	97	94	92	90	94	92	90	88	86
Hm	0.46Hm	0.46Hm	4.0	102	99	97	95	101	98	96	94	99	97	95	93	96	95	93	92	89
			5.0	103	101	99	97	102	100	98	97	100	98	97	95	98	96	95	94	91
			7.0	105	103	102	100	103	102	101	99	101	100	99	98	99	98	97	96	93
			10.0	106	105	103	102	104	103	102	101	102	101	100	100	100	99	99	98	95

