

# 屋内照明器具特性

|         |                   |          |
|---------|-------------------|----------|
| 品番 (品名) | LGB76485          |          |
| 光源      | LED5000_70_710 ×1 | 710.0 1m |
| 管理番号    | K0160345(0)D 1    |          |
| BZ分類    | BZ1               |          |

| 器具効率   | 100%            | 天井      | 80%           |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |    |
|--------|-----------------|---------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
|        |                 |         | 70            | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  |     |    |
| 上方光束   | 0%              | 反射率     | 壁             | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |
| 下方光束   | 100%            |         | 床             | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |
|        |                 | 室指数     | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |
| 保守率    | 良 0.67          | 0.6     | 88            | 83  | 80  | 77  | 87  | 83  | 79  | 77  | 86  | 82  | 79  | 77  | 85  | 81  | 79  | 77  | 76  |    |
|        | 中 0.63          | 0.8     | 93            | 88  | 85  | 83  | 92  | 88  | 85  | 83  | 91  | 87  | 84  | 82  | 89  | 86  | 84  | 82  | 81  |    |
|        | 否 0.56          | 1.0     | 96            | 92  | 89  | 86  | 95  | 91  | 88  | 86  | 93  | 90  | 88  | 86  | 92  | 89  | 87  | 85  | 84  |    |
| 下方投影面積 | cm <sup>2</sup> | 1.25    | 98            | 95  | 92  | 90  | 97  | 94  | 91  | 89  | 96  | 93  | 91  | 89  | 94  | 92  | 90  | 88  | 87  |    |
|        |                 | 1.5     | 100           | 97  | 94  | 92  | 99  | 96  | 94  | 92  | 97  | 95  | 93  | 91  | 96  | 94  | 92  | 90  | 89  |    |
| 等価発光面積 | cm <sup>2</sup> | 2.0     | 102           | 99  | 97  | 95  | 101 | 99  | 97  | 95  | 99  | 97  | 95  | 94  | 97  | 96  | 94  | 93  | 91  |    |
|        |                 | 2.5     | 103           | 101 | 99  | 97  | 102 | 100 | 98  | 97  | 100 | 99  | 97  | 96  | 99  | 97  | 96  | 95  | 93  |    |
| 取付高さ   | 器具間隔最大限         |         | 3.0           | 104 | 102 | 100 | 99  | 103 | 101 | 100 | 98  | 101 | 100 | 98  | 97  | 99  | 98  | 97  | 94  |    |
|        | 横方向 (A)         | 縦方向 (B) | 4.0           | 105 | 104 | 102 | 101 | 104 | 103 | 101 | 100 | 102 | 101 | 100 | 99  | 100 | 99  | 98  | 95  |    |
| Hm     | 0.36Hm          | 0.37Hm  | 5.0           | 106 | 105 | 103 | 102 | 105 | 104 | 102 | 102 | 103 | 102 | 101 | 100 | 101 | 100 | 99  | 96  |    |
|        |                 |         | 7.0           | 107 | 106 | 105 | 104 | 105 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 101 | 101 | 100 | 97  |    |
|        |                 |         | 10.0          | 107 | 106 | 106 | 105 | 106 | 105 | 105 | 104 | 104 | 103 | 103 | 102 | 102 | 101 | 101 | 98  |    |

