

屋内照明器具特性	
品番 (品名)	LGB81422Z
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1 m
管理番号	K0169328(0)DR1
BZ分類	BZ4/1.1/BZ5/6.0/BZ6

器具効率	89%	反射率	天井	80%				70%				50%				30%				0%			
	上方光束		26%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
	下方光束		63%	床	10%				10%				10%				10%				0%		
		室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	50	40	34	29	47	38	33	29	43	36	31	27	39	33	29	25	22			
	中	0.63	0.8	57	47	41	36	54	46	40	35	49	42	37	33	44	38	34	31	27			
	否	0.56	1.0	62	53	46	42	59	51	45	40	53	46	41	38	47	42	38	35	30			
			1.25	66	58	52	47	63	55	50	45	57	51	46	42	51	46	42	39	34			
下方投影面積			1.5	69	62	56	51	66	59	54	49	59	54	49	46	53	49	45	42	36			
	等価発光面積		2.0	74	67	62	57	70	64	59	55	63	58	54	51	57	53	50	47	40			
取付高さ	器具間隔最大限		2.5	77	71	66	62	73	68	63	59	66	61	58	55	59	56	53	50	43			
	横方向 (A)	縦方向 (B)	3.0	79	73	69	65	75	70	66	63	67	64	60	58	61	58	55	53	45			
Hm	1.12Hm	1.09Hm	4.0	81	77	73	70	77	73	70	67	70	67	64	62	63	61	58	56	48			
			5.0	83	79	76	73	79	76	73	70	71	69	66	64	64	62	60	59	50			
			7.0	85	82	79	77	81	78	76	74	73	71	69	68	66	65	63	62	53			
			10.0	86	84	82	80	83	81	79	77	75	73	72	71	68	67	65	64	55			

