

屋内照明器具特性	
品番 (品名)	LGB81785
光源	LED2700_70_3780 x1 3780.0 lm
管理番号	K0161534(0)DR1
BZ分類	BZ8

器具効率	100%	天井	80%				70%				50%				30%				0%
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	50%	床	10%				10%				10%				10%				0%
下方光束	50%	室指数	照明率 (X0.01)																ZCM
保守率	良 中 否 0.63 0.6 0.56	0.6	45	33	25	19	41	30	23	18	34	25	19	15	27	20	16	12	7
		0.8	54	41	33	27	49	38	31	25	40	32	26	21	32	26	21	17	11
		1.0	59	48	39	33	54	44	37	31	45	37	31	26	36	30	25	22	14
		1.25	65	54	46	40	59	50	43	37	49	42	36	31	40	34	30	26	17
下方投影面積	cm ²	1.5	69	59	51	45	63	54	47	42	52	46	40	35	42	37	33	29	19
		2.0	75	66	59	53	69	61	54	49	57	51	46	42	46	42	38	35	23
取付高さ	器具間隔最大限		2.5	78	70	64	58	72	65	59	54	60	55	50	46	49	45	42	26
	横方向 (A)	縦方向 (B)	3.0	81	74	68	63	75	68	63	58	62	58	54	50	51	48	44	28
1.5m	2.45m	2.17m	4.0	84	79	73	69	78	73	68	64	66	62	58	55	54	51	48	32
2	3.24	2.73	5.0	86	82	77	73	80	76	72	68	68	64	61	58	56	53	51	34
2.5	4.02	3.31	7.0	89	85	82	78	83	79	76	73	70	67	65	63	58	56	54	37
3	4.81	3.91	10.0	91	88	86	83	85	82	80	77	72	70	68	66	60	59	57	40

