

屋内照明器具特性

品番 (品名)	LGB84326		
光源	LED2700_70_507 ×1	507.0 lm	
管理番号	K0135905 (0) DB1		
BZ分類	BZ1		

器具効率	100%	反射率	天井				80%				70%				50%				30%				0%
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10					
上方光束	0%																						
下方光束	100%		10%				10%				10%				10%				0%				
室指数			照明率 (X0.01)																ZCM				
保守率	良	0.67	0.6	84	78	74	71	83	78	74	71	82	77	74	71	81	76	73	71	70			
	中	0.63	0.8	90	84	80	78	89	84	80	78	87	83	80	77	86	82	79	77	76			
	否	0.56	1.0	93	88	85	82	92	88	84	82	90	87	84	81	89	86	83	81	80			
下方投影面積	cm ²	1.25	96	92	88	86	95	91	88	86	93	90	87	85	92	89	86	85	83				
		1.5	98	94	91	89	97	93	91	88	95	92	90	88	93	91	89	87	85				
等価発光面積	cm ²	2.0	101	97	95	93	100	97	94	92	98	95	93	91	96	94	92	90	89				
		2.5	102	99	97	95	101	99	96	95	99	97	95	94	97	95	94	93	91				
取付高さ	器具間隔最大限		3.0	103	101	99	97	102	100	98	96	100	98	97	95	98	97	95	94	92			
	横方向 (A)	縦方向 (B)	4.0	104	103	101	100	103	102	100	99	101	100	99	97	99	98	97	96	94			
Hm	0.41Hm	0.41Hm	5.0	105	104	102	101	104	103	102	100	102	101	100	99	100	99	98	97	95			
			7.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99	96			
			10.0	107	106	105	104	106	105	104	103	104	103	102	101	101	100	100	99	97			

