

# 屋内照明器具特性

|         |                   |  |          |  |  |
|---------|-------------------|--|----------|--|--|
| 品番 (品名) | LGBX54000         |  |          |  |  |
| 光源      | LED2700_70_375 x1 |  | 375.0 lm |  |  |
| 管理番号    | K0153622(0)DB1    |  |          |  |  |
| BZ分類    | BZ5/3.5/BZ6       |  |          |  |  |

|                |                    |                    |                  |     |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    |    |     |
|----------------|--------------------|--------------------|------------------|-----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|----|----|-----|
| 器具効率           | 100%               | 天井                 | 80%              |     |    |     | 70% |    |    |     | 50% |    |    |     | 30% |    |    |     | 0% |    |     |
|                | 上方光束               |                    | 27%              | 反射率 | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30 | 10 | 0%  |
|                | 下方光束               |                    | 73%              |     | 床  | 10% |     |    |    | 10% |     |    |    | 10% |     |    |    | 10% |    |    |     |
| 室指数            | 照明率 ( X0.01 )      |                    |                  |     |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    |    | ZCM |
| 保守率            | 良                  | 0.67               | 0.6              | 53  | 41 | 34  | 28  | 50 | 40 | 33  | 28  | 45 | 36 | 30  | 26  | 41 | 33 | 28  | 25 | 21 |     |
|                | 中                  | 0.63               | 0.8              | 62  | 51 | 43  | 37  | 59 | 49 | 41  | 36  | 53 | 45 | 39  | 34  | 48 | 41 | 36  | 32 | 27 |     |
|                | 否                  | 0.56               | 1.0              | 68  | 57 | 50  | 44  | 64 | 55 | 48  | 42  | 58 | 50 | 44  | 40  | 52 | 46 | 41  | 37 | 32 |     |
|                |                    |                    | 1.25             | 73  | 63 | 56  | 50  | 70 | 61 | 54  | 49  | 63 | 56 | 50  | 46  | 56 | 51 | 46  | 42 | 36 |     |
| 下方投影面積         | c m <sup>2</sup>   |                    | 1.5              | 77  | 68 | 61  | 55  | 73 | 65 | 59  | 53  | 66 | 60 | 54  | 50  | 60 | 54 | 50  | 46 | 40 |     |
|                | 等価発光面積             |                    | c m <sup>2</sup> | 2.0 | 82 | 74  | 68  | 63 | 78 | 71  | 65  | 61 | 71 | 65  | 60  | 56 | 64 | 59  | 55 | 52 | 45  |
| 取付高さ           | 器具間隔最大限            |                    | 2.5              | 86  | 79 | 73  | 68  | 82 | 75 | 70  | 66  | 74 | 69 | 65  | 61  | 67 | 63 | 59  | 56 | 48 |     |
|                | 横方向 (A)            | 縦方向 (B)            | 3.0              | 88  | 82 | 77  | 72  | 84 | 78 | 74  | 69  | 76 | 72 | 68  | 64  | 69 | 65 | 62  | 59 | 51 |     |
| H <sub>m</sub> | 1.29H <sub>m</sub> | 1.28H <sub>m</sub> | 4.0              | 91  | 86 | 82  | 78  | 87 | 82 | 78  | 75  | 79 | 75 | 72  | 69  | 72 | 69 | 66  | 64 | 55 |     |
|                |                    |                    | 5.0              | 93  | 89 | 85  | 81  | 89 | 85 | 81  | 78  | 81 | 78 | 75  | 72  | 73 | 71 | 69  | 66 | 57 |     |
|                |                    |                    | 7.0              | 95  | 92 | 89  | 86  | 91 | 88 | 85  | 83  | 83 | 81 | 78  | 76  | 76 | 74 | 72  | 70 | 61 |     |
|                |                    |                    | 10.0             | 97  | 95 | 92  | 90  | 93 | 91 | 89  | 87  | 85 | 83 | 81  | 80  | 77 | 76 | 75  | 73 | 63 |     |

