

屋内照明器具特性

品番 (品名)	LGBZ1405									
光源	LED6200_70_4100 x1 4100.0 lm									
管理番号	K0154972(0)D 1									
BZ分類	BZ5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	2 %																			
下方光束	98 %																			
室指数	照明率 (X0.01)																ZCM			
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56
		0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56
下方投影面積	c m ²		1.25	78	68	60	54	76	66	59	54	72	64	58	53	69	62	57	52	50
	等価発光面積		c m ²	1.5	82	73	65	60	80	71	65	59	77	69	63	58	73	67	62	58
取付高さ	器具間隔最大限		2.5	91	84	79	74	89	83	78	73	86	81	76	72	83	78	74	71	68
	横方向 (A)	縦方向 (B)	3.0	94	88	83	78	92	86	82	77	89	84	80	76	85	81	78	75	72
H m	1.31H m	1.31H m	4.0	97	92	88	84	95	91	87	83	92	88	85	82	89	86	83	80	77
			5.0	99	95	91	88	97	94	90	87	94	91	88	85	91	88	86	84	81
			7.0	101	98	95	93	100	97	94	92	97	94	92	90	94	92	90	88	85
			10.0	103	101	99	97	102	100	98	96	99	97	95	94	96	94	93	92	88

