

屋内照明器具特性

品番 (品名)	LGBZ1429															
光源	LED6200_70_4100 x1 4100.0 lm															
管理番号	K0161808(0)D 1															
BZ分類	BZ6/0.7/BZ5															

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	3 %																			
下方光束	97 %																			
室指数	照明率 (X0.01) ZCM																			
保守率	良	0.63	0.6	53	41	32	27	52	40	32	26	49	38	31	26	47	37	31	26	24
	中	0.6	0.8	63	51	43	37	62	50	42	36	59	49	41	36	56	47	41	36	33
	否	0.56	1.0	70	59	50	44	68	58	50	44	65	56	49	43	62	54	48	43	40
			1.25	76	66	58	52	74	65	57	51	71	62	56	50	67	60	54	50	47
下方投影面積	c m ²		1.5	81	71	63	57	79	70	63	57	75	67	61	56	71	65	60	55	52
等価発光面積	c m ²		2.0	86	78	71	66	84	77	71	65	81	74	69	64	77	72	67	63	60
取付高さ	器具間隔最大限		2.5	90	83	77	72	88	82	76	71	84	79	74	70	81	76	72	69	65
	横方向 (A)	縦方向 (B)	3.0	93	86	81	76	91	85	80	76	87	82	78	74	84	80	76	73	69
H m	1.46 H m	1.46 H m	4.0	96	91	87	82	94	90	85	82	91	87	83	80	87	84	81	78	75
			5.0	98	94	90	87	96	92	89	86	93	90	87	84	90	87	84	82	78
			7.0	101	97	94	92	99	96	93	91	96	93	91	88	92	90	88	86	83
			10.0	103	100	98	96	101	99	97	95	98	96	94	92	95	93	92	90	86

