

屋内照明器具特性	
品番 (品名)	LGBZ1442K
光源	LED6500_70_3800 x1 3800.0 lm
管理番号	K0138135(0)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		13%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		87%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.63	0.6	0.6	55	43	35	30	53	42	35	30	49	40	33	29	46	38	32	28	25
	中	0.6	0.6	0.6	65	53	46	40	62	52	45	39	58	49	43	38	54	47	41	37	34
	否	0.56	0.56	0.56	71	61	53	47	69	59	52	47	64	56	50	45	60	53	48	44	40
	0.56	0.56	0.56	77	67	60	54	74	66	59	54	70	62	56	52	65	59	54	50	46	
下方投影面積	c m <sup>2</sup>		1.25	77	67	60	54	74	66	59	54	70	62	56	52	65	59	54	50	46	
	等価発光面積		c m <sup>2</sup>	1.5	81	72	65	60	78	70	64	59	73	67	61	57	69	63	59	55	51
取付高さ	器具間隔最大限		2.0	87	79	73	68	84	77	72	67	79	73	68	64	74	69	65	62	57	
	横方向 (A)	縦方向 (B)	2.5	90	84	78	74	87	81	77	72	82	77	73	70	77	73	70	67	62	
1.5m	1.96m	1.96m	3.0	92	87	82	78	90	85	80	76	84	80	77	73	80	76	73	70	65	
2	2.56	2.56	4.0	95	91	87	84	93	89	85	82	88	84	81	79	83	80	78	75	70	
2.5	3.17	3.17	5.0	97	94	90	87	95	91	88	85	90	87	84	82	85	82	80	78	73	
3	3.8	3.79	7.0	100	97	94	92	97	94	92	90	92	90	88	86	87	85	84	82	76	
			10.0	101	99	97	95	99	97	95	93	94	92	91	89	89	88	86	85	79	

