

屋内照明器具特性

品番 (品名)	LGBZ1616															
光源	LED6200_70_4100 x1 4100.0 lm															
管理番号	K0161881(1)D 1															
BZ分類	BZ6/0.7/BZ5															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	3%	室指数																			
下方光束	97%	照明率 (X0.01)																			
保守率	良 0.63 中 0.6 否 0.56	ZCM																			
		0.6	5.4	4.1	3.3	2.7	5.2	4.0	3.2	2.7	4.9	3.9	3.2	2.7	4.7	3.8	3.1	2.6	2.4		
下方投影面積	c m ²	1.25	7.6	6.6	5.8	5.2	7.5	6.5	5.7	5.2	7.1	6.3	5.6	5.1	6.8	6.0	5.5	5.0	4.7		
		1.5	8.1	7.1	6.4	5.8	7.9	7.0	6.3	5.7	7.5	6.7	6.1	5.6	7.2	6.5	6.0	5.5	5.2		
等価発光面積	c m ²	2.0	8.7	7.8	7.2	6.6	8.5	7.7	7.1	6.6	8.1	7.4	6.9	6.4	7.7	7.2	6.7	6.3	6.0		
		2.5	9.0	8.3	7.7	7.2	8.8	8.2	7.6	7.1	8.5	7.9	7.4	7.0	8.1	7.6	7.2	6.9	6.6		
取付高さ	器具間隔最大限																				
	横方向 (A)	縦方向 (B)																			
H m	1.42 H m	1.42 H m	3.0	9.3	8.7	8.1	7.6	9.1	8.5	8.0	7.6	8.7	8.2	7.8	7.4	8.4	8.0	7.6	7.3	7.0	
			4.0	9.6	9.1	8.7	8.3	9.4	9.0	8.5	8.2	9.1	8.7	8.3	8.0	8.7	8.4	8.1	7.8	7.5	
			5.0	9.8	9.4	9.0	8.7	9.6	9.3	8.9	8.6	9.3	9.0	8.7	8.4	9.0	8.7	8.4	8.2	7.8	
			7.0	10.1	9.8	9.4	9.2	9.9	9.6	9.3	9.1	9.6	9.3	9.1	8.9	9.2	9.0	8.8	8.6	8.3	
			10.0	10.3	10.0	9.8	9.6	10.1	9.9	9.7	9.5	9.8	9.6	9.4	9.2	9.5	9.3	9.2	9.0	8.6	

