

屋内照明器具特性	
品番 (品名)	LGBZ2430
光源	LED6200_70_4899 x1 4899.0 lm
管理番号	K0147626(0)DB1
BZ分類	BZ6/0.7/BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	10%	床	10%				10%				10%				10%				0%	
下方光束	90%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	53	40	32	26	51	39	31	26	47	37	30	25	44	35	29	24	22
	中	0.6	0.8	62	50	42	36	60	49	41	36	56	47	40	35	52	44	38	34	30
	否	0.56	1.0	69	58	49	43	67	56	48	43	62	53	47	41	58	51	45	40	37
			1.25	75	65	57	51	73	63	56	50	68	60	53	48	64	57	51	47	43
下方投影面積	cm ²		1.5	79	70	62	56	77	68	61	55	72	64	59	54	67	61	56	52	48
等価発光面積	cm ²		2.0	85	77	70	65	82	75	69	64	78	71	66	62	73	68	63	59	55
取付高さ	器具間隔最大限		2.5	89	82	76	71	86	80	74	69	81	76	71	67	77	72	68	65	60
	横方向 (A)	縦方向 (B)	3.0	91	85	80	75	89	83	78	74	84	79	75	71	79	75	72	69	64
1.5m	2.16m	2.16m	4.0	95	90	85	81	92	88	83	80	87	83	80	77	83	79	77	74	69
2	2.86	2.86	5.0	97	93	89	85	94	90	87	84	89	86	83	81	85	82	80	77	72
2.5	3.55	3.55	7.0	99	96	93	90	97	94	91	89	92	90	87	85	87	85	84	82	76
3	4.24	4.24	10.0	101	99	97	94	99	97	94	93	94	92	90	89	90	88	87	85	80

