

屋内照明器具特性

品番 (品名)	LGBZ3358K														
光源	LED2700_70_4500 x1 4500.0 lm														
管理番号	K0154925(0)D 1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%			
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
				床	10%				10%				10%				10%				0%	
上方光束	8%	室指数	照明率 (X0.01)																ZCM			
下方光束	92%																					
保守率	良 中 否	0.63	0.6	0.56	0.6	55	43	35	29	53	42	34	29	50	40	33	29	47	38	32	28	26
		0.6	0.8	65	53	45	39	63	52	44	39	59	50	43	38	56	48	42	37	34		
		0.56	1.0	71	60	52	46	69	59	52	46	65	56	50	45	61	54	48	44	41		
			1.25	77	67	60	54	75	66	59	53	71	63	57	52	67	60	55	51	47		
下方投影面積	c m ²	1.5	81	72	65	59	79	70	64	58	74	67	62	57	70	64	60	55	52			
		2.0	87	79	73	67	84	77	71	66	80	74	69	65	76	71	67	63	59			
取付高さ	器具間隔最大限		2.5	90	83	78	73	88	82	76	72	83	78	74	70	79	75	71	68	64		
	横方向 (A)	縦方向 (B)	3.0	93	87	82	77	90	85	80	76	86	81	77	74	82	78	75	72	67		
H m	1.26 H m	1.26 H m	4.0	96	91	87	83	94	89	85	82	89	86	82	79	85	82	79	77	72		
			5.0	98	94	90	87	96	92	89	85	91	88	85	83	87	85	82	80	75		
			7.0	100	97	94	92	98	95	93	90	94	91	89	87	90	88	86	84	79		
			10.0	102	100	98	96	100	98	96	94	96	94	92	91	92	90	89	88	83		

