

屋内照明器具特性	
品番 (品名)	LGC45806
光源	LED6500_70_4000 x1 4000.0 lm
管理番号	K0157519(0)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	12%	床	10%				10%				10%				10%				0%				
下方光束	88%	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	5.4	4.2	3.4	2.9	5.2	4.1	3.3	2.8	4.9	3.9	3.2	2.7	4.5	3.7	3.1	2.7	2.4			
	中	0.6	0.8	6.4	5.2	4.4	3.8	6.1	5.1	4.3	3.8	5.7	4.8	4.2	3.7	5.4	4.6	4.0	3.5	3.2			
	否	0.56	1.0	7.0	5.9	5.1	4.5	6.8	5.8	5.0	4.5	6.3	5.5	4.8	4.3	5.9	5.2	4.6	4.2	3.8			
			1.25	7.6	6.6	5.8	5.2	7.3	6.4	5.7	5.1	6.9	6.1	5.5	5.0	6.4	5.8	5.3	4.8	4.4			
下方投影面積	cm ²		1.5	8.0	7.1	6.3	5.8	7.7	6.9	6.2	5.7	7.2	6.5	6.0	5.5	6.8	6.2	5.7	5.3	4.9			
等価発光面積	cm ²		2.0	8.5	7.8	7.1	6.6	8.3	7.6	7.0	6.5	7.8	7.2	6.7	6.2	7.3	6.8	6.4	6.0	5.6			
取付高さ	器具間隔最大限		2.5	8.9	8.2	7.6	7.1	8.6	8.0	7.5	7.0	8.1	7.6	7.2	6.8	7.6	7.2	6.8	6.5	6.0			
	横方向 (A)	縦方向 (B)	3.0	9.1	8.5	8.0	7.6	8.9	8.3	7.9	7.4	8.4	7.9	7.5	7.2	7.9	7.5	7.2	6.9	6.4			
1.5m	1.96m	1.97m	4.0	9.5	9.0	8.6	8.2	9.2	8.8	8.4	8.0	8.7	8.3	8.0	7.7	8.2	7.9	7.6	7.4	6.9			
2	2.58	2.6	5.0	9.7	9.3	8.9	8.6	9.4	9.0	8.7	8.4	8.9	8.6	8.3	8.0	8.4	8.2	7.9	7.7	7.2			
2.5	3.21	3.24	7.0	9.9	9.6	9.3	9.0	9.6	9.4	9.1	8.8	9.2	8.9	8.7	8.5	8.7	8.5	8.3	8.1	7.6			
3	3.76	3.79	10.0	10.1	9.9	9.6	9.4	9.8	9.6	9.4	9.2	9.3	9.2	9.0	8.8	8.9	8.7	8.6	8.5	7.9			

