

# 屋内照明器具特性

品番 (品名)	L G W 8 0 3 5 4									
光源	LED2700_70_197.8 ×1					197.8 1 m				
管理番号	K0141568 ( 0 ) DR 1									
B Z 分類	B Z 6									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	52 %	反射率	床		10 %		10 %		10 %		10 %		10 %		10 %		10 %		0 %	
下方光束	48 %		室指数	照明率 ( X 0 . 0 1 )																Z C M
保守率	良 中 否 0.63 0.6 0.56	0.6	4.8	3.6	2.9	2.4	4.4	3.4	2.7	2.2	3.7	2.9	2.3	1.9	3.0	2.4	2.0	1.6	1.1	
		0.8	5.7	4.5	3.8	3.2	5.2	4.2	3.5	3.0	4.3	3.6	3.0	2.6	3.5	3.0	2.6	2.2	1.6	
		1.0	6.3	5.2	4.4	3.9	5.8	4.8	4.1	3.6	4.8	4.1	3.6	3.1	3.9	3.4	3.0	2.7	1.9	
		1.25	6.8	5.8	5.1	4.5	6.3	5.4	4.8	4.2	5.2	4.6	4.1	3.7	4.3	3.8	3.4	3.1	2.2	
下方投影面積	c m <sup>2</sup>	1.5	7.2	6.3	5.6	5.1	6.6	5.8	5.2	4.7	5.5	5.0	4.5	4.1	4.6	4.1	3.8	3.5	2.4	
		2.0	7.7	7.0	6.4	5.8	7.1	6.5	5.9	5.5	6.0	5.5	5.1	4.7	4.9	4.6	4.2	4.0	2.8	
取付高さ	器具間隔最大限		2.5	8.1	7.4	6.9	6.4	7.5	6.9	6.4	6.0	6.3	5.8	5.5	5.1	5.2	4.9	4.6	4.3	3.1
	横方向 ( A )	縦方向 ( B )	3.0	8.3	7.7	7.2	6.8	7.7	7.2	6.7	6.3	6.5	6.1	5.8	5.5	5.4	5.1	4.8	4.6	3.3
H m	1.39 H m	1.31 H m	4.0	8.6	8.2	7.7	7.4	8.0	7.6	7.2	6.9	6.8	6.4	6.2	5.9	5.6	5.4	5.2	5.0	3.6
			5.0	8.8	8.4	8.1	7.7	8.2	7.8	7.5	7.2	6.9	6.7	6.4	6.2	5.8	5.6	5.4	5.2	5.0
			7.0	9.1	8.7	8.5	8.2	8.4	8.1	7.9	7.6	7.1	6.9	6.7	6.6	5.9	5.8	5.7	5.5	4.0
			10.0	9.2	9.0	8.8	8.6	8.6	8.4	8.2	8.0	7.3	7.2	7.0	6.9	6.1	6.0	5.9	5.8	4.2

