

屋内照明器具特性

品番 (品名)	L G W 8 5 0 0 6 Z														
光源	LDA4L - G - E17 / Z40E / S / W / 2 × 1										440.0 1 m				
管理番号	K0160308 (0) DR 1														
BZ分類	BZ6														

器具効率	56 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	13 %	室指数	照明率 (X0.01)															ZCM			
下方光束	43 %																				
保守率	良 中 否 0.63 0.6 0.56	0.6	28	21	17	13	27	20	16	13	24	18	15	12	21	17	14	11	9		
		0.8	33	26	22	18	32	25	21	18	28	23	20	17	25	21	18	16	13		
		1.0	37	30	26	22	35	29	25	21	31	27	23	20	28	24	21	19	16		
		1.25	40	34	30	26	38	33	28	25	34	30	26	24	31	27	24	22	19		
下方投影面積	c m ²	1.5	42	37	32	29	40	35	31	28	36	32	29	26	33	29	27	24	21		
		2.0	45	41	37	34	43	39	35	33	39	36	33	30	35	33	30	28	24		
取付高さ	器具間隔最大限		2.5	48	43	40	37	45	42	38	36	41	38	35	33	37	35	33	31	27	
	横方向 (A)	縦方向 (B)	3.0	49	45	42	39	47	43	41	38	43	40	37	35	39	36	35	33	28	
H m	1.40 H m	1.40 H m	4.0	51	48	45	43	49	46	44	41	44	42	40	38	40	39	37	36	31	
			5.0	52	50	47	45	50	48	45	44	46	44	42	40	42	40	39	37	33	
			7.0	53	52	50	48	51	49	48	46	47	46	44	43	43	42	41	40	35	
			10.0	55	53	52	50	52	51	50	49	48	47	46	45	44	43	43	42	37	

