

屋内照明器具特性

品番 (品名)	L G W 8 5 2 4 1 Y															
光源	LED3500_70_530 ×1 530.0 l m															
管理番号	K0161779 (0) DB 1															
B Z 分類	B Z 5															

器具効率	49 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	3 %	室指数	照明率 (X 0.01)																Z C M		
下方光束	46 %																				
保守率	良 中 否 0.63 0.6 0.56	0.6	2.7	2.1	1.7	1.4	2.6	2.0	1.7	1.4	2.5	2.0	1.6	1.4	2.3	1.9	1.6	1.4	1.2		
		0.8	3.2	2.6	2.2	1.9	3.1	2.5	2.2	1.9	2.9	2.4	2.1	1.9	2.7	2.3	2.0	1.8	1.7		
		1.0	3.5	3.0	2.6	2.3	3.4	2.9	2.5	2.2	3.2	2.8	2.4	2.2	3.0	2.6	2.4	2.1	2.0		
		1.25	3.8	3.3	2.9	2.6	3.7	3.2	2.9	2.6	3.5	3.1	2.8	2.5	3.3	2.9	2.7	2.5	2.3		
下方投影面積	c m ²	1.5	4.0	3.5	3.2	2.9	3.9	3.5	3.1	2.9	3.7	3.3	3.0	2.8	3.5	3.2	2.9	2.7	2.5		
		2.0	4.3	3.9	3.6	3.3	4.1	3.8	3.5	3.2	3.9	3.6	3.4	3.2	3.7	3.5	3.3	3.1	2.9		
取付高さ	器具間隔最大限		2.5	4.4	4.1	3.8	3.6	4.3	4.0	3.7	3.5	4.1	3.8	3.6	3.4	3.9	3.7	3.5	3.3		
	横方向 (A)	縦方向 (B)	3.0	4.6	4.3	4.0	3.8	4.4	4.2	3.9	3.7	4.2	4.0	3.8	3.6	4.0	3.8	3.7	3.5	3.3	
H m	1.27 H m	1.27 H m	4.0	4.7	4.5	4.3	4.1	4.6	4.4	4.2	4.0	4.4	4.2	4.0	3.9	4.2	4.0	3.9	3.8	3.5	
			5.0	4.8	4.6	4.4	4.3	4.7	4.5	4.3	4.2	4.5	4.3	4.2	4.1	4.3	4.2	4.0	3.9	3.7	
			7.0	4.9	4.8	4.6	4.5	4.8	4.7	4.5	4.4	4.6	4.5	4.4	4.3	4.4	4.3	4.2	4.1	3.9	
			10.0	5.0	4.9	4.8	4.7	4.9	4.8	4.7	4.6	4.7	4.6	4.5	4.5	4.4	4.4	4.3	4.1	3.9	

