

屋内照明器具特性

品番 (品名)	L G W C 7 1 6 2 2	
光源	LED2700_70_310 x1	310.0 l m
管理番号	K0157035 (0) D 1	
B Z 分類	B Z 3 / 1 . 1 / B Z 2	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
下方光束	100 %	床		10 %				10 %				10 %				10 %				0 %			
室指数			照明率 (X 0 . 0 1)																				Z C M
保守率	良	0.67	0.6	64	53	47	42	63	53	46	42	61	52	46	42	59	51	46	42	40			
	中	0.63	0.8	75	65	59	54	73	64	58	54	71	63	58	54	69	62	57	53	52			
	否	0.56	1.0	81	73	67	62	80	72	66	62	78	71	66	62	75	69	65	61	59			
			1.25	87	79	74	70	86	79	74	69	83	77	73	69	81	76	72	68	67			
下方投影面積	c m ²		1.5	90	84	79	75	89	83	78	75	87	81	77	74	84	80	76	73	71			
	等価発光面積		c m ²	2.0	95	90	86	82	94	89	85	82	91	87	84	81	89	85	83	80	78		
取付高さ	器具間隔最大限		2.5	98	93	90	87	97	92	89	86	94	91	88	85	92	89	86	84	82			
	横方向 (A)	縦方向 (B)	3.0	100	96	93	90	98	95	92	89	96	93	90	88	94	91	89	87	85			
H m	1.16 H m	1.20 H m	4.0	102	99	96	94	101	98	96	93	98	96	94	92	96	94	92	91	88			
			5.0	103	101	99	97	102	100	98	96	100	98	96	94	97	96	94	93	91			
			7.0	105	103	101	100	103	102	100	99	101	100	98	97	99	98	97	96	93			
			10.0	106	105	103	102	105	103	102	101	102	101	100	100	100	99	98	98	95			

