

屋内照明器具特性	
品番 (品名)	NDW06300BK
光源	LED5000_70_510 x1 510.0 lm
管理番号	K0158587(0)DB1
BZ分類	BZ4/1.1/BZ3

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	60	48	41	36	59	48	41	36	56	47	40	36	54	46	40	36	34
	中	0.63	0.8	70	60	53	48	69	59	52	47	67	58	52	47	64	57	51	47	45
	否	0.56	1.0	77	68	61	56	76	67	61	56	73	66	60	55	71	64	59	55	53
			1.25	83	75	69	64	82	74	68	64	79	73	67	63	77	71	66	63	61
下方投影面積		cm ²	1.5	87	80	74	70	86	79	74	69	83	77	73	69	81	76	72	68	66
等価発光面積		cm ²	2.0	93	87	82	78	91	86	81	77	89	84	80	76	86	82	79	76	73
取付高さ	器具間隔最大限		2.5	96	91	87	83	95	90	86	82	92	88	84	81	89	86	83	81	78
	横方向 (A)	縦方向 (B)	3.0	98	94	90	87	97	93	89	86	94	91	88	85	92	89	86	84	82
Hm	1.25Hm	1.25Hm	4.0	101	97	94	92	99	96	93	91	97	94	92	90	94	92	90	88	86
			5.0	102	99	97	95	101	98	96	94	98	96	94	92	96	94	93	91	88
			7.0	104	102	100	98	103	101	99	97	100	99	97	96	98	97	95	94	92
			10.0	105	104	102	101	104	103	101	100	102	100	99	98	99	98	98	97	94

