

屋内照明器具特性

品番 (品名)	NNF 4 1 8 8 6									
光源	LED_FULLL4000_85_4620 ×1					4620.0 1 m				
管理番号	K0157493 (0) DB 1									
BZ分類	BZ6 / 0.7 / BZ5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		66 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		34 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.83	0.6	47	36	29	24	42	33	26	22	34	27	22	18	26	21	17	15	9	
	中	0.81	0.8	56	45	38	33	50	41	35	30	40	34	29	25	31	26	23	20	12	
	否	0.77	1.0	62	52	45	40	56	47	41	36	45	39	34	30	35	30	27	24	15	
			1.25	67	58	52	46	61	53	47	43	49	43	39	36	38	34	31	29	18	
下方投影面積			1.5	71	63	57	52	65	58	52	48	52	47	43	40	40	37	34	32	20	
			2.0	77	70	64	60	69	64	59	55	56	52	48	45	43	41	38	36	22	
取付高さ	器具間隔最大限		2.5	80	74	69	65	72	67	63	60	59	55	52	49	46	43	41	39	24	
	横方向 (A)	縦方向 (B)	3.0	82	77	73	69	75	70	67	63	60	57	55	52	47	45	43	42	26	
1.5m	1.66 m	2.15 m	4.0	85	81	77	74	77	74	71	68	63	60	58	56	49	47	46	45	27	
2	2.2	2.77	5.0	87	83	80	78	79	76	74	71	64	62	60	59	50	49	48	46	29	
2.5	2.75	3.41	7.0	89	86	84	82	81	79	77	75	66	64	63	62	52	51	50	49	30	
3	3.29	4.06	10.0	90	89	87	85	82	81	79	78	67	66	65	64	53	52	51	51	31	

