

屋内照明器具特性	
品番 (品名)	NNF 4 2 0 4 5 J
光源	LDL40S. WW/ 27 / 20 (2000 A) × 2 2000.0 1 m
管理番号	K0124923 (1) DR 1
BZ分類	BZ6

器具効率	99 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	11 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	88 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.93 0.9 0.86	0.6	52	40	32	26	50	39	31	26	47	37	30	25	44	35	29	24	22	
		0.8	61	49	41	35	59	48	40	35	55	46	39	34	51	43	37	33	29	
		1.0	68	56	48	42	65	55	47	41	61	52	45	40	57	49	43	39	35	
		1.25	73	63	55	49	71	61	54	48	66	58	52	46	62	55	49	45	41	
下方投影面積	c m ²	1.5	77	68	60	54	75	66	59	53	70	62	56	51	65	59	54	50	45	
		2.0	83	75	68	62	80	73	66	61	75	69	63	59	71	65	61	57	52	
取付高さ	器具間隔最大限		2.5	87	79	73	68	84	77	71	67	79	73	68	64	74	69	65	62	57
	横方向 (A)	縦方向 (B)	3.0	89	83	77	72	87	81	75	71	81	76	72	68	77	72	69	65	60
1.5m	2.1 m	2.11 m	4.0	93	87	83	78	90	85	81	77	85	81	77	74	80	77	74	71	65
2	2.77	2.65	5.0	95	90	86	82	92	88	84	81	87	84	80	77	82	79	77	74	69
2.5	3.45	3.21	7.0	97	94	90	87	95	91	88	86	90	87	84	82	85	83	81	79	73
3	4.11	3.79	10.0	99	97	94	92	97	94	92	90	92	90	88	86	87	85	84	82	77

