

# 屋内照明器具特性

品番 (品名)	NNF 4 2 2 6 3									
光源	LDL40S.N/19/25(2500A) ×2      2500.0 l m									
管理番号	K0137461(0)DB1									
BZ分類	BZ6/0.7/BZ5									

器具効率	91%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	5%	室指数																		照明率 ( X0.01 )																		ZCM																	
下方光束	86%																																																						
保守率	良 中 否	0.81	0.6	49	37	30	25	47	37	30	25	45	35	29	24	42	34	28	24	22																																			
		0.77	0.8	58	47	40	34	56	46	39	34	53	44	38	33	50	43	37	33	30																																			
			1.0	64	54	46	41	62	53	46	41	59	51	45	40	56	49	43	39	37																																			
		0.68	1.25	70	60	53	48	68	59	53	47	64	57	51	47	61	55	50	46	43																																			
下方投影面積	c m <sup>2</sup>	1.5	74	65	58	53	72	64	58	53	68	61	56	52	65	59	54	51	48																																				
		2.0	79	72	66	61	77	70	65	61	73	68	63	59	70	65	61	58	55																																				
等価発光面積	c m <sup>2</sup>	2.5	82	76	71	67	80	75	70	66	77	72	68	64	73	70	66	63	60																																				
		3.0	85	79	75	71	83	78	74	70	79	75	72	68	76	73	70	67	63																																				
取付高さ	器具間隔最大限		4.0	88	84	80	77	86	82	79	76	83	79	76	74	79	77	74	72	68																																			
	横方向 (A)	縦方向 (B)	5.0	90	86	83	80	88	85	82	79	85	82	80	77	81	79	77	75	72																																			
1.5m	2.24 m	2.13 m	7.0	92	89	87	85	90	88	86	84	87	85	83	82	84	82	81	79	76																																			
2	2.95	2.69	10.0	94	92	90	89	92	90	89	87	89	87	86	85	86	85	84	82	79																																			
2.5	3.67	3.27																																																					
3	4.38	3.86																																																					

