

屋内照明器具特性	
品番 (品名)	NNF 4 3 5 0 0
光源	LDL40S.N/14/26(2600A) ×3 2600.0 l m
管理番号	K0126754(1)DR1
BZ分類	BZ5

器具効率	92%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	92%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.81 中 0.77 否 0.68	0.6	52	40	33	28	50	40	33	28	48	39	32	27	46	38	32	27	25	
		0.8	61	50	43	37	60	49	42	37	57	48	42	37	55	47	41	37	35	
		1.0	67	57	50	44	66	56	49	44	63	55	49	44	60	53	48	43	41	
		1.25	73	64	57	51	71	63	56	51	68	61	55	51	66	60	54	50	48	
下方投影面積	c m ²	1.5	77	69	62	57	75	68	61	57	72	66	60	56	70	64	59	55	53	
		2.0	82	75	70	65	81	74	69	65	78	72	68	64	75	71	67	63	61	
取付高さ	器具間隔最大限		2.5	86	80	75	70	84	79	74	70	81	77	73	69	79	75	71	68	66
	横方向 (A)	縦方向 (B)	3.0	88	83	78	75	87	82	78	74	84	80	76	73	81	78	75	72	70
1.5m	2.09 m	2.13 m	4.0	91	87	83	80	90	86	83	80	87	84	81	78	84	82	79	77	75
2	2.74	2.68	5.0	93	89	86	84	91	88	86	83	89	86	84	82	86	84	82	80	78
2.5	3.41	3.26	7.0	95	92	90	88	94	91	89	87	91	89	87	86	89	87	86	84	82
3	4.07	3.85	10.0	96	95	93	91	95	94	92	91	93	91	90	89	91	89	88	87	85

