

屋内照明器具特性

品番 (品名)	NNF 4 2 7 0 4 J				
光源	LDL40S.N/19/25-K ×2 2500.0 lm				
管理番号	K0126774 (1) DR 1				
BZ分類	BZ5/0.7/BZ4				

器具効率	61 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	0 %	室指数																		
下方光束	61 %	照明率 (X0.01)																		
保守率	良 中 否	0.77	0.6	3.6	2.8	2.4	2.0	3.5	2.8	2.3	2.0	3.3	2.7	2.3	2.0	3.2	2.7	2.3	2.0	1.9
		0.72	0.8	4.2	3.5	3.0	2.7	4.1	3.4	3.0	2.7	3.9	3.4	3.0	2.7	3.8	3.3	2.9	2.7	2.5
		0.68	1.0	4.6	3.9	3.5	3.2	4.5	3.9	3.5	3.1	4.3	3.8	3.4	3.1	4.2	3.7	3.4	3.1	3.0
			1.25	4.9	4.4	3.9	3.6	4.8	4.3	3.9	3.6	4.7	4.2	3.9	3.6	4.5	4.1	3.8	3.5	3.4
			1.5	5.2	4.7	4.3	3.9	5.1	4.6	4.2	3.9	4.9	4.5	4.2	3.9	4.7	4.4	4.1	3.9	3.7
下方投影面積		2.0	5.5	5.1	4.7	4.5	5.4	5.0	4.7	4.4	5.2	4.9	4.6	4.4	5.1	4.8	4.5	4.3	4.2	
等価発光面積		2.5	5.7	5.4	5.1	4.8	5.6	5.3	5.0	4.8	5.5	5.2	4.9	4.7	5.3	5.0	4.8	4.6	4.5	
取付高さ	器具間隔最大限		3.0	5.9	5.6	5.3	5.0	5.8	5.5	5.2	5.0	5.6	5.4	5.1	4.9	5.4	5.2	5.0	4.9	4.7
	横方向 (A)	縦方向 (B)	4.0	6.1	5.8	5.6	5.4	6.0	5.7	5.5	5.3	5.8	5.6	5.4	5.3	5.6	5.5	5.3	5.2	5.0
1.5m	1.84m	2.11m	5.0	6.2	6.0	5.8	5.6	6.1	5.9	5.7	5.6	5.9	5.8	5.6	5.5	5.8	5.6	5.5	5.4	5.2
2	2.43	2.64	7.0	6.3	6.1	6.0	5.9	6.2	6.1	5.9	5.8	6.1	5.9	5.8	5.7	5.9	5.8	5.7	5.6	5.5
2.5	3.02	3.2	10.0	6.4	6.3	6.2	6.1	6.3	6.2	6.1	6.0	6.2	6.1	6.0	5.9	6.0	5.9	5.9	5.8	5.6
3	3.61	3.78																		

