

屋内照明器具特性	
品番 (品名)	NNF W4 2 0 5 1 K
光源	LDL40S . N / 29 / 31 - 9 ( 3150 A ) × 2      3150.0 1 m
管理番号	K0125111 ( 0 ) DR 1
BZ分類	BZ6 / 0.7 / BZ5

器具効率	97 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	10 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	87 %	室指数	照明率 ( X0.01 )																ZCM	
保守率	良 中 否 0.93 0.9 0.86	0.6	52	39	32	26	50	39	31	26	46	37	30	25	43	35	29	25	22	
		0.8	61	49	41	36	59	48	41	35	55	46	39	34	51	43	38	33	30	
		1.0	67	56	48	42	65	55	47	42	61	52	46	41	57	49	44	39	36	
		1.25	73	63	55	49	70	61	54	48	66	58	52	47	62	55	50	46	42	
下方投影面積	c m <sup>2</sup>	1.5	77	68	60	55	74	66	59	54	70	63	57	52	65	59	55	50	47	
		2.0	82	74	68	63	80	73	67	62	75	69	64	60	71	66	61	58	53	
取付高さ	器具間隔最大限		2.5	86	79	73	68	83	77	72	67	79	73	69	65	74	70	66	63	58
	横方向 ( A )	縦方向 ( B )	3.0	88	82	77	73	86	80	76	71	81	76	72	69	77	73	69	66	62
1.5m	2.11 m	2.11 m	4.0	92	87	82	79	89	85	81	77	84	81	77	74	80	77	74	72	67
2	2.78	2.65	5.0	94	90	86	82	91	87	84	81	86	83	81	78	82	80	77	75	70
2.5	3.45	3.21	7.0	96	93	90	87	94	91	88	86	89	87	84	82	85	83	81	79	74
3	4.12	3.78	10.0	98	96	93	91	96	93	91	90	91	89	88	86	87	85	84	83	77

