

屋内照明器具特性	
品番 (品名)	NNF W4 2 5 0 0 K
光源	LDL40S . N / 29 / 31 - 9 ( 3150 A ) × 2      3150.0 1 m
管理番号	K0125113 ( 2 ) DR 1
BZ分類	BZ6 / 0.7 / BZ5 / 8.5 / BZ6

器具効率	70 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	8 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	62 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 ( X0.01 )																ZCM	
保守率	良 中 否	0.86	0.6	37	29	23	19	36	28	23	19	33	26	22	18	31	25	21	18	16
		0.81	0.8	44	36	30	26	42	35	29	25	39	33	28	25	37	31	27	24	22
			1.0	48	40	35	31	47	39	34	30	44	37	33	29	41	35	31	28	26
		0.76	1.25	52	45	40	35	51	44	39	35	47	42	37	34	44	39	36	33	30
下方投影面積	c m <sup>2</sup>	1.5	55	49	43	39	53	47	42	39	50	45	41	37	47	42	39	36	33	
		2.0	59	54	49	45	57	52	48	44	54	49	46	43	50	47	44	41	38	
取付高さ	器具間隔最大限		2.5	62	57	53	49	60	55	51	48	56	52	49	46	53	50	47	44	41
	横方向 ( A )	縦方向 ( B )	3.0	64	59	55	52	62	58	54	51	58	55	52	49	55	52	49	47	44
1.5m	2.01 m	2.23 m	4.0	66	62	59	56	64	61	58	55	60	58	55	53	57	55	53	51	47
2	2.64	2.78	5.0	67	64	61	59	65	63	60	58	62	60	57	55	58	57	55	53	49
2.5	3.28	3.35	7.0	69	67	64	62	67	65	63	61	64	62	60	59	60	59	57	56	52
3	3.92	3.94	10.0	70	69	67	65	69	67	65	64	65	64	62	61	62	61	60	59	54

