

屋内照明器具特性

品番 (品名)	NNF W4 2 7 0 1 K														
光源	LDL40S.N/14/26(2600A) ×2 2600.0 1 m														
管理番号	K0125106(0)DR1														
BZ分類	BZ5														

器具効率	95 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 (X0.01)																ZCM		
下方光束	95 %																				
保守率	良 0.81 中 0.77 否 0.68	0.6	5.2	4.0	3.3	2.8	5.1	4.0	3.3	2.7	4.9	3.9	3.2	2.7	4.7	3.8	3.2	2.7	2.5		
		0.8	6.2	5.1	4.3	3.7	6.0	5.0	4.2	3.7	5.8	4.8	4.2	3.7	5.5	4.7	4.1	3.7	3.5		
		1.0	6.8	5.8	5.0	4.4	6.7	5.7	5.0	4.4	6.4	5.5	4.9	4.4	6.1	5.4	4.8	4.3	4.1		
		1.25	7.4	6.4	5.7	5.2	7.2	6.3	5.7	5.1	6.9	6.2	5.6	5.1	6.7	6.0	5.5	5.0	4.8		
下方投影面積	c m ²	1.5	7.8	6.9	6.3	5.7	7.6	6.8	6.2	5.7	7.3	6.6	6.1	5.6	7.1	6.5	6.0	5.6	5.3		
		2.0	8.4	7.6	7.0	6.5	8.2	7.5	7.0	6.5	7.9	7.3	6.8	6.4	7.6	7.1	6.7	6.4	6.1		
取付高さ	器具間隔最大限		2.5	8.7	8.1	7.6	7.1	8.6	8.0	7.5	7.1	8.3	7.8	7.3	7.0	8.0	7.6	7.2	6.9	6.6	
	横方向 (A)	縦方向 (B)	3.0	9.0	8.4	7.9	7.5	8.8	8.3	7.9	7.5	8.5	8.1	7.7	7.4	8.3	7.9	7.6	7.3	7.0	
1.5m	2.13 m	2.13 m	4.0	9.3	8.8	8.5	8.1	9.1	8.7	8.4	8.1	8.9	8.5	8.2	7.9	8.6	8.3	8.1	7.8	7.6	
2	2.81	2.68	5.0	9.5	9.1	8.8	8.5	9.3	9.0	8.7	8.4	9.1	8.8	8.5	8.3	8.8	8.6	8.4	8.2	7.9	
2.5	3.49	3.24	7.0	9.7	9.4	9.2	9.0	9.6	9.3	9.1	8.9	9.3	9.1	8.9	8.7	9.1	8.9	8.7	8.6	8.3	
3	4.16	3.82	10.0	9.9	9.7	9.5	9.3	9.7	9.6	9.4	9.2	9.5	9.3	9.2	9.1	9.3	9.1	9.0	8.9	8.6	

