

屋内照明器具特性	
品番 (品名)	NNF W4 2 7 2 0 K
光源	LDL40S.N/14/26(2600A) ×2 2600.0 1 m
管理番号	K0125046(0)DR1
BZ分類	BZ5

器具効率	85 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	85 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否	0.81	0.6	47	36	29	25	46	36	29	25	44	35	29	24	42	34	28	24	23
		0.77	0.8	55	45	38	33	54	45	38	33	52	43	37	33	49	42	37	33	31
			1.0	61	52	45	40	60	51	44	40	57	49	44	39	55	48	43	39	37
		0.68	1.25	66	58	51	46	65	57	51	46	62	55	50	46	60	54	49	45	43
下方投影面積	c m ²	1.5	70	62	56	51	68	61	55	51	66	59	54	50	63	58	54	50	48	
		2.0	75	68	63	59	73	67	62	58	71	66	61	58	68	64	60	57	55	
取付高さ	器具間隔最大限		2.5	78	72	68	64	77	71	67	63	74	70	66	62	71	68	65	62	59
	横方向 (A)	縦方向 (B)	3.0	80	75	71	67	79	74	70	67	76	72	69	66	74	71	68	65	63
1.5m	2.16 m	2.12 m	4.0	83	79	76	73	82	78	75	72	79	76	73	71	77	74	72	70	68
2	2.84	2.66	5.0	85	81	79	76	83	80	78	75	81	79	76	74	79	77	75	73	71
2.5	3.52	3.22	7.0	87	84	82	80	85	83	81	79	83	81	80	78	81	79	78	77	74
3	4.2	3.79	10.0	88	86	85	83	87	85	84	82	85	83	82	81	83	82	81	80	77

