

屋内照明器具特性	
品番 (品名)	NNF W4 2 0 0 1 K
光源	LDL40S . N / 29 / 31 - 9 ( 3150 A ) × 2      3150 . 0 1 m
管理番号	K0125030 ( 0 ) DR 1
B Z 分類	BZ6

器具効率	96 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	15 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	81 %	室指数	照明率 ( X0.01 )																				ZCM
保守率	良 中 否 0.93 0.9 0.86	0.6	50	38	30	25	48	37	30	24	44	35	28	23	41	32	27	23	20				
		0.8	59	47	39	33	57	46	38	33	52	43	36	31	48	40	35	30	27				
		1.0	65	54	46	40	62	52	45	39	57	49	42	37	53	46	40	36	32				
		1.25	70	60	52	46	68	58	51	45	62	55	48	43	58	51	46	41	37				
下方投影面積	c m <sup>2</sup>	1.5	74	65	57	51	71	63	56	50	66	59	53	48	61	55	50	46	41				
		2.0	80	71	65	59	77	69	63	58	71	65	60	55	66	61	56	53	47				
取付高さ	器具間隔最大限		2.5	83	76	70	65	80	74	68	63	74	69	64	60	69	65	61	57	52			
	横方向 ( A )	縦方向 ( B )	3.0	86	79	74	69	83	77	72	67	77	72	68	64	72	68	64	61	55			
1.5m	2.09 m	2.1 m	4.0	89	84	79	75	86	81	77	73	80	76	73	69	75	72	69	66	60			
2	2.75	2.64	5.0	91	87	82	79	88	84	80	77	82	79	76	73	77	74	72	69	63			
2.5	3.43	3.2	7.0	94	90	87	84	91	87	84	82	85	82	80	77	80	77	75	73	67			
3	4.09	3.77	10.0	95	93	90	88	93	90	88	86	87	85	83	81	82	80	78	77	70			

