

# 屋内照明器具特性

品番 (品名)	NNLK21509 + FSK21020 + NNL20	
光源	LED4000_85_600 ×1	600.0 l m
管理番号	K0139114 (4) DR 1	
BZ分類	BZ6	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	15 %	反射率	床	10 %				10 %				10 %				10 %				0 %			
下方光束	85 %		室指数	照明率 ( X0.01 )																			
保守率	良 中 否	0.81	0.6	52	39	31	25	50	38	30	25	46	36	29	24	42	33	27	23	20			
		0.77	0.8	61	49	40	34	58	47	39	33	54	44	37	32	50	41	35	31	27			
			1.0	67	55	47	41	64	54	46	40	59	50	44	38	55	47	41	37	33			
		0.68	1.25	73	62	54	48	70	60	52	47	65	56	50	45	60	53	47	43	38			
下方投影面積	c m <sup>2</sup>	1.5	77	67	59	53	74	65	57	52	68	61	54	49	63	57	52	47	42				
		2.0	83	74	67	61	79	72	65	60	74	67	62	57	68	63	58	54	49				
取付高さ	器具間隔最大限		2.5	86	79	72	67	83	76	70	65	77	71	66	62	72	67	63	59	53			
	横方向 (A)	縦方向 (B)	3.0	89	82	76	71	86	79	74	69	80	75	70	66	74	70	66	63	57			
1.5m	1.64 m	1.95 m	4.0	92	87	82	77	89	84	79	75	83	79	75	72	78	74	71	68	62			
2	2.18	2.57	5.0	94	90	85	81	91	87	83	79	85	82	79	75	80	77	74	72	65			
2.5	2.73	3.19	7.0	97	93	90	87	94	91	87	84	88	85	83	80	83	80	78	76	70			
3	3.26	3.82	10.0	99	96	94	91	96	94	91	89	90	88	86	84	85	83	82	80	73			

