

屋内照明器具特性

品番 (品名)	NNLK21509 + FSK21020 + NNL21														
光源	LED4000_85_1040 x1 1040.0 lm														
管理番号	K0139114 (4) DR1														
BZ分類	BZ6														

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		15%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		85%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01) ZCM																				
保守率	良	0.81	0.6	52	39	31	25	50	38	30	25	46	36	29	24	42	33	27	23	20	
	中	0.77	0.8	61	49	40	34	58	47	39	33	54	44	37	32	50	41	35	31	27	
	否	0.68	1.0	67	55	47	41	64	54	46	40	59	50	44	38	55	47	41	37	33	
	下方投影面積		1.25	73	62	54	48	70	60	52	47	65	56	50	45	60	53	47	43	38	
等価発光面積		1.5	77	67	59	53	74	65	57	52	68	61	54	49	63	57	52	47	42		
		2.0	83	74	67	61	79	72	65	60	74	67	62	57	68	63	58	54	49		
取付高さ	器具間隔最大限		2.5	86	79	72	67	83	76	70	65	77	71	66	62	72	67	63	59	53	
	横方向 (A)	縦方向 (B)	3.0	89	82	76	71	86	79	74	69	80	75	70	66	74	70	66	63	57	
1.5m	1.64m	1.95m	4.0	92	87	82	77	89	84	79	75	83	79	75	72	78	74	71	68	62	
2	2.18	2.57	5.0	94	90	85	81	91	87	83	79	85	82	79	75	80	77	74	72	65	
2.5	2.73	3.19	7.0	97	93	90	87	94	91	87	84	88	85	83	80	83	80	78	76	70	
3	3.26	3.82	10.0	99	96	94	91	96	94	91	89	90	88	86	84	85	83	82	80	73	

