

屋内照明器具特性	
品番 (品名)	NNLK41509 + FSK41020 + NNL43
光源	LED3000_85_2150 x1 2150.0 lm
管理番号	K0139114 (4) DR1
BZ分類	BZ6

器具効率	100%	天井	80%				70%				50%				30%				0%			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	15%	床	10%				10%				10%				10%				0%			
下方光束	85%	室指数	照明率 (X0.01) ZCM																			
保守率	良 0.81 中 0.77 否 0.68	0.6	52	39	31	25	50	38	30	25	46	36	29	24	42	33	27	23	20			
		0.8	61	49	40	34	58	47	39	33	54	44	37	32	50	41	35	31	27			
		1.0	67	55	47	41	64	54	46	40	59	50	44	38	55	47	41	37	33			
		1.25	73	62	54	48	70	60	52	47	65	56	50	45	60	53	47	43	38			
下方投影面積	cm ²	1.5	77	67	59	53	74	65	57	52	68	61	54	49	63	57	52	47	42			
		2.0	83	74	67	61	79	72	65	60	74	67	62	57	68	63	58	54	49			
取付高さ	器具間隔最大限		2.5	86	79	72	67	83	76	70	65	77	71	66	62	72	67	63	59	53		
	横方向 (A)	縦方向 (B)	3.0	89	82	76	71	86	79	74	69	80	75	70	66	74	70	66	63	57		
1.5m	1.67m	2.16m	4.0	92	87	82	77	89	84	79	75	83	79	75	72	78	74	71	68	62		
2	2.21	2.72	5.0	94	90	85	81	91	87	83	79	85	82	79	75	80	77	74	72	65		
2.5	2.74	3.3	7.0	97	93	90	87	94	91	87	84	88	85	83	80	83	80	78	76	70		
3	3.28	3.9	10.0	99	96	94	91	96	94	91	89	90	88	86	84	85	83	82	80	73		

