

屋内照明器具特性

品番 (品名)	NNLK41515 + NNL4500ENT									
光源	LED5000_85_5200 x1 5200.0lm									
管理番号	K0128261 (*) DB1									
BZ分類	BZ5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	4 %																			
下方光束	96 %																			
室指数	照明率 (X0.01) ZCM																			
保守率	良 0.83 中 0.81 否 0.77	0.6	55	42	34	29	53	41	34	28	50	40	33	28	48	39	32	28	25	
		0.8	64	53	44	38	63	52	44	38	59	50	43	38	56	48	42	37	35	
		1.0	71	60	52	46	69	59	51	45	65	56	50	45	62	54	49	44	41	
		1.25	77	67	59	53	75	65	58	52	71	63	57	52	68	61	55	51	48	
下方投影面積	c m ²	1.5	81	72	64	58	79	70	63	58	75	68	62	57	71	65	60	56	53	
		2.0	87	79	72	67	85	77	71	66	81	74	69	65	77	72	67	63	60	
取付高さ	器具間隔最大限		2.5	90	83	77	72	88	82	76	72	84	79	74	70	81	76	72	69	65
	横方向 (A)	縦方向 (B)	3.0	93	87	81	77	91	85	80	76	87	82	78	74	83	79	76	73	69
1.5m	2 m	2.19 m	4.0	96	91	87	83	94	90	85	82	90	86	83	80	87	83	81	78	74
2	2.64	2.76	5.0	98	94	90	87	96	92	89	86	92	89	86	83	89	86	84	81	78
2.5	3.29	3.35	7.0	101	97	94	92	99	96	93	90	95	93	90	88	92	89	88	86	82
3	3.93	3.96	10.0	102	100	98	96	101	98	96	94	97	95	93	92	94	92	91	89	85

