

屋内照明器具特性

品番 (品名)	NNLK41515 + NNL4606HWT									
光源	LED4000_85_6240 x1 6240.0 lm									
管理番号	K0135570 (2) DB1									
BZ分類	BZ4/1.8/BZ5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																	
		床	10 %				10 %				10 %				10 %				0 %																																	
上方光束	4 %	室指数																	照明率 (X0.01)																	ZCM																
下方光束	96 %																																																			
保守率	良 中 否	0.83	0.6	5.9	4.7	4.0	3.4	5.7	4.6	3.9	3.4	5.4	4.5	3.8	3.4	5.2	4.4	3.8	3.3	3.1																																
		0.81	0.8	6.8	5.7	5.0	4.4	6.6	5.6	4.9	4.4	6.3	5.4	4.8	4.3	6.0	5.3	4.7	4.3	4.0																																
		0.77	1.0	7.4	6.4	5.7	5.1	7.2	6.3	5.6	5.1	6.9	6.1	5.5	5.0	6.6	5.9	5.4	4.9	4.7																																
			1.25	8.0	7.0	6.4	5.8	7.8	6.9	6.3	5.8	7.4	6.7	6.1	5.7	7.1	6.5	6.0	5.6	5.3																																
下方投影面積	c m ²	1.5	8.4	7.5	6.8	6.3	8.2	7.4	6.8	6.3	7.8	7.1	6.6	6.2	7.5	6.9	6.4	6.1	5.8																																	
		2.0	8.9	8.2	7.6	7.1	8.7	8.0	7.5	7.0	8.3	7.8	7.3	6.9	8.0	7.5	7.1	6.8	6.4																																	
取付高さ	器具間隔最大限		2.5	9.2	8.6	8.1	7.6	9.0	8.4	8.0	7.5	8.6	8.2	7.7	7.4	8.3	7.9	7.5	7.2	6.9																																
	横方向 (A)	縦方向 (B)	3.0	9.4	8.9	8.4	8.0	9.2	8.7	8.3	7.9	8.9	8.5	8.1	7.7	8.5	8.2	7.9	7.6	7.2																																
1.5m	1.46 m	2.11 m	4.0	9.7	9.3	8.9	8.6	9.5	9.1	8.8	8.5	9.2	8.8	8.5	8.3	8.8	8.6	8.3	8.1	7.7																																
2	1.94	2.65	5.0	9.9	9.5	9.2	8.9	9.7	9.4	9.1	8.8	9.4	9.1	8.8	8.6	9.0	8.8	8.6	8.4	8.0																																
2.5	2.41	3.22	7.0	10.1	9.8	9.6	9.3	9.9	9.7	9.4	9.2	9.6	9.4	9.2	9.0	9.3	9.1	8.9	8.8	8.4																																
3	2.89	3.81	10.0	10.3	10.1	9.9	9.7	10.1	9.9	9.7	9.6	9.8	9.6	9.5	9.3	9.4	9.3	9.2	9.1	8.7																																

