

屋内照明器具特性

品番 (品名)	NNLK41517+NNL4200SWT														
光源	LED4000_85_2240 x1 2240.0 1m														
管理番号	K0135565(0)DB1														
BZ分類	BZ4														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	1%	反射率	床	10%				10%				10%				10%				0%
下方光束	99%		室指数	照明率 (X0.01) ZCM																
保守率	良 0.81 中 0.77 否 0.68	0.6	60	48	41	36	59	48	41	36	56	47	40	36	54	46	40	36	34	
		0.8	70	59	52	46	68	58	51	46	66	57	51	46	63	56	50	46	44	
		1.0	76	66	59	54	74	65	59	53	72	64	58	53	69	62	57	53	51	
		1.25	82	73	66	61	80	72	66	61	77	70	65	60	75	69	64	60	58	
下方投影面積	c m ²	1.5	85	77	71	66	84	76	71	66	81	75	70	65	78	73	68	65	62	
		2.0	91	84	79	74	89	83	78	74	86	81	77	73	84	79	75	72	70	
取付高さ	器具間隔最大限		2.5	94	88	83	79	92	87	83	79	90	85	81	78	87	83	80	77	75
	横方向 (A)	縦方向 (B)	3.0	96	91	87	83	95	90	86	83	92	88	85	82	89	86	83	81	78
1.5m	1.47m	2.11m	4.0	99	95	92	89	98	94	91	88	95	92	89	87	92	90	88	85	83
2	1.95	2.67	5.0	101	98	95	92	99	96	94	91	97	94	92	90	94	92	90	88	86
2.5	2.43	3.24	7.0	103	100	98	96	101	99	97	95	99	97	95	94	96	95	93	92	89
3	2.91	3.83	10.0	104	103	101	99	103	101	100	99	100	99	98	97	98	97	96	95	92

