


屋内照明器具特性	
品番 (品名)	NNQ37030
光源	LEDRGBW_70_4587.9 ×1 4587.9 lm
管理番号	K0163806(0)DR1
BZ分類	BZ10

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	100%	床	10%				10%				10%				10%				0%	
下方光束	0%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	43	33	26	22	37	28	23	19	25	19	16	13	14	11	9	8	0
	中	0.63	0.8	51	41	34	29	43	35	29	25	29	24	21	18	17	14	12	10	0
	否	0.56	1.0	56	47	40	35	48	40	35	31	33	28	24	22	19	16	14	13	0
			1.25	61	53	46	42	52	45	40	36	36	31	28	25	20	18	16	15	0
下方投影面積		cm ²	1.5	65	57	51	46	56	49	44	40	38	34	31	28	22	20	18	17	0
等価発光面積		cm ²	2.0	70	63	58	54	60	55	50	47	41	38	35	33	24	22	21	19	0
取付高さ	器具間隔最大限		2.5	73	67	63	59	63	58	54	51	43	40	38	36	25	23	22	21	0
	横方向 (A)	縦方向 (B)	3.0	75	70	66	62	64	61	57	54	44	42	40	38	26	24	23	22	0
1.5m	0.3m	0.3m	4.0	78	74	70	67	67	64	61	59	46	44	43	41	27	26	25	24	0
2	0.4	0.4	5.0	79	76	73	71	68	66	63	61	47	46	44	43	27	27	26	25	0
2.5	0.5	0.5	7.0	81	79	77	75	70	68	66	65	49	47	46	45	28	28	27	27	0
3	0.6	0.6	10.0	83	81	80	78	72	70	69	68	50	49	48	47	29	28	28	28	0



直射水平面照度	80 lx
	60
	40
	20
	10
	8
	6
	4
	2
	.8
	.6
	.4
	.2
	8m 6 4 2 0 2 4 6 8