

屋内照明器具特性

品番(品名)	NNY21558	
光源	LED3000_70_1940 ×1 1940.0 1m	
管理番号	K0140014(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		下方光束 100%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.69	0.6	94	90	88	86	93	90	88	86	92	89	87	86	92	89	87	86	85
	中	0.67	0.8	98	94	92	90	97	94	92	90	96	93	91	90	95	93	91	90	89
	否	0.63	1.0	100	97	95	93	99	96	94	93	98	96	94	93	97	95	93	92	91
下方投影面積 等価発光面積	cm ²	1.25	1.02	99	97	96	101	99	97	95	100	98	96	95	98	97	95	94	93	
		1.5	1.03	101	99	97	102	100	98	97	101	99	98	96	99	98	97	96	95	
		2.0	1.04	103	101	100	104	102	101	99	102	101	100	99	100	99	98	98	96	
取付高さ	器具間隔最大限		2.5	1.05	104	103	102	104	103	102	101	103	102	101	100	101	100	100	99	97
	横方向(A)	縦方向(B)	3.0	1.06	105	104	103	105	104	103	102	103	102	101	101	101	100	100	98	
1.5m	0.43m	1.18m	4.0	1.07	106	105	104	106	105	104	104	104	103	103	102	102	101	101	99	
2	0.57	1.2	5.0	1.07	106	106	105	106	106	105	105	104	104	103	103	102	102	102	99	
2.5	0.7	1.24	7.0	1.08	107	107	107	107	106	106	106	105	104	104	104	103	103	102	100	
3	0.83	1.33	10.0	1.08	108	108	108	108	107	107	107	107	105	105	105	105	103	103	100	

