

# 屋内照明器具特性

|         |                         |           |
|---------|-------------------------|-----------|
| 品番 (品名) | NSEK47612J + NNL4200EVT |           |
| 光源      | LED3500_85_2250 ×1      | 2250.0 lm |
| 管理番号    | K0145988 (0) DB 1       |           |
| BZ分類    | BZ5                     |           |

| 器具効率   | 100 %           | 天井      | 80 % |               |     |     | 70 % |      |     |    | 50 % |      |    |    | 30 % |      |    |    | 0 % |     |  |  |  |
|--------|-----------------|---------|------|---------------|-----|-----|------|------|-----|----|------|------|----|----|------|------|----|----|-----|-----|--|--|--|
|        |                 |         | 壁    | 70            | 50  | 30  | 10   | 70   | 50  | 30 | 10   | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10  | 0 % |  |  |  |
| 上方光束   | 0 %             | 反射率     | 床    | 10 %          |     |     |      | 10 % |     |    |      | 10 % |    |    |      | 10 % |    |    |     | 0 % |  |  |  |
| 下方光束   | 100 %           |         | 室指数  | 照明率 ( X0.01 ) |     |     |      |      |     |    |      |      |    |    |      |      |    |    |     |     |  |  |  |
| 保守率    | 良               | 0.81    | 0.6  | 57            | 44  | 36  | 31   | 55   | 44  | 36 | 31   | 53   | 43 | 36 | 31   | 51   | 42 | 35 | 31  | 29  |  |  |  |
|        | 中               | 0.77    | 0.8  | 67            | 55  | 47  | 41   | 65   | 54  | 47 | 41   | 62   | 53 | 46 | 41   | 60   | 52 | 46 | 41  | 39  |  |  |  |
|        | 否               | 0.68    | 1.0  | 73            | 63  | 55  | 49   | 72   | 62  | 54 | 49   | 69   | 60 | 54 | 48   | 66   | 59 | 53 | 48  | 46  |  |  |  |
|        |                 |         | 1.25 | 79            | 70  | 62  | 57   | 78   | 69  | 62 | 56   | 75   | 67 | 61 | 56   | 72   | 65 | 60 | 55  | 53  |  |  |  |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5  | 83            | 75  | 68  | 62   | 82   | 74  | 67 | 62   | 79   | 72 | 66 | 61   | 76   | 70 | 65 | 61  | 58  |  |  |  |
| 等価発光面積 | cm <sup>2</sup> |         | 2.0  | 89            | 82  | 76  | 71   | 88   | 81  | 75 | 70   | 84   | 79 | 74 | 70   | 82   | 77 | 72 | 69  | 66  |  |  |  |
| 取付高さ   | 器具間隔最大限         |         | 2.5  | 93            | 86  | 81  | 77   | 91   | 85  | 80 | 76   | 88   | 83 | 79 | 75   | 85   | 81 | 77 | 74  | 72  |  |  |  |
|        | 横方向 (A)         | 縦方向 (B) | 3.0  | 95            | 90  | 85  | 81   | 94   | 89  | 84 | 80   | 91   | 86 | 83 | 79   | 88   | 84 | 81 | 78  | 76  |  |  |  |
| 1.5m   | 1.98m           | 2.15m   | 4.0  | 98            | 94  | 90  | 87   | 97   | 93  | 89 | 86   | 94   | 91 | 88 | 85   | 91   | 88 | 86 | 83  | 81  |  |  |  |
| 2      | 2.62            | 2.7     | 5.0  | 100           | 97  | 93  | 90   | 99   | 96  | 92 | 90   | 96   | 93 | 91 | 88   | 93   | 91 | 89 | 87  | 84  |  |  |  |
| 2.5    | 3.26            | 3.28    | 7.0  | 102           | 100 | 97  | 95   | 101  | 99  | 96 | 94   | 98   | 96 | 94 | 93   | 96   | 94 | 93 | 91  | 88  |  |  |  |
| 3      | 3.89            | 3.87    | 10.0 | 104           | 102 | 100 | 99   | 103  | 101 | 99 | 98   | 100  | 99 | 97 | 96   | 98   | 97 | 95 | 94  | 91  |  |  |  |

