

屋内照明器具特性

品番 (品名)	NYY65943+NYY91300B+NTS90	
光源	LED3000_70_2060 x1 2060.0lm	
管理番号	K0164960(9)DJ1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	
上方光束	0%	反射率	10%				10%				10%				10%				0%
下方光束	100%		室指数	照明率 (X0.01)															
保守率	良 0.67	0.6	92	88	85	83	91	87	85	83	90	87	85	83	89	86	84	83	82
	中 0.63	0.8	96	92	90	88	95	92	89	88	94	91	89	87	93	91	89	87	86
	否 0.56	1.0	99	95	93	91	98	95	93	91	97	94	92	90	95	93	91	90	89
下方投影面積 等価発光面積	cm ²	1.25	101	98	95	94	100	97	95	93	98	96	94	93	97	95	94	92	91
		1.5	102	99	97	95	101	99	97	95	100	97	96	95	98	96	95	94	93
		2.0	104	101	100	98	103	101	99	98	101	99	98	97	99	98	97	96	94
取付高さ	器具間隔最大限		2.5	105	103	101	100	104	102	100	99	102	100	99	100	99	98	97	95
	横方向 (A)	縦方向 (B)	3.0	105	104	102	101	104	103	102	100	102	101	100	99	101	100	99	96
Hm	0.77Hm	0.77Hm	4.0	106	105	104	103	105	104	103	102	103	102	101	101	100	100	99	97
			5.0	107	106	105	104	106	105	104	103	103	103	102	101	102	101	100	98
			7.0	107	106	106	105	106	105	104	104	103	103	102	102	102	101	101	98
			10.0	108	107	106	106	106	105	105	104	104	104	103	102	102	102	101	99

