

屋内照明器具特性

品番 (品名)	S F 9 9 6 Z	
光源	LDA5 L - G / K40 E / S / W ×1	485.0 l m
管理番号	K0129912 (0) DB 1	
B Z 分類	BZ10	

器具効率	54 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		34 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		20 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																			Z C M	
保守率	良	0.67	0.6	23	16	12	9	20	14	10	8	15	11	8	6	11	8	6	4	1	
	中	0.63	0.8	27	20	16	12	24	18	14	11	18	14	11	8	13	10	8	6	2	
	否	0.56	1.0	30	23	19	15	27	21	17	14	21	16	13	11	15	12	9	7	2	
下方投影面積 等価発光面積	c m ²	1.25	33	27	22	19	29	24	20	17	23	19	15	13	17	14	11	9	3		
		1.5	35	29	25	21	31	26	22	19	24	20	17	15	18	15	13	11	4		
		2.0	38	33	29	25	34	30	26	23	27	23	20	18	20	17	15	13	6		
取付高さ	器具間隔最大限		2.5	40	35	32	29	36	32	29	26	28	25	23	20	21	19	17	15	7	
	横方向 (A)	縦方向 (B)	3.0	41	37	34	31	37	34	31	28	29	27	24	22	22	20	18	17	8	
H m	0.00H m	0.00H m	4.0	43	40	37	34	39	36	33	31	31	29	27	25	24	22	20	19	10	
			5.0	44	42	39	37	40	38	35	33	32	30	28	27	25	23	22	20	11	
			7.0	46	44	42	40	42	40	38	36	34	32	31	29	26	25	23	22	12	
			10.0	47	45	44	42	43	41	40	39	35	33	32	31	27	26	25	24	14	

