

屋内照明器具特性	
品番 (品名)	S F X 5 0 1
光源	LED2700_70_860 ×1 860.0 l m
管理番号	K0160350(0)DR1
BZ分類	BZ10

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	84 %	床	10 %				10 %				10 %				10 %				0 %
下方光束	16 %	室指数	照明率 (X0.01)																ZCM
保守率	良 中 否 0.63 0.6 0.56	0.6	43	31	24	19	37	28	21	17	27	20	16	12	17	13	10	8	0
		0.8	50	39	32	27	44	35	28	23	32	25	21	17	20	16	13	11	1
		1.0	56	46	38	33	49	40	34	29	35	29	25	21	23	19	16	13	2
		1.25	61	52	44	39	53	45	39	34	39	33	29	25	25	21	19	16	3
下方投影面積	c m ²	1.5	65	56	49	44	57	49	43	39	41	36	32	28	27	23	21	18	3
		2.0	70	63	56	51	61	55	50	45	45	40	37	33	29	26	24	22	5
取付高さ	器具間隔最大限		2.5	74	67	61	56	64	59	54	50	47	43	40	37	31	29	26	6
	横方向 (A)	縦方向 (B)	3.0	76	70	65	60	67	62	57	53	49	45	42	40	32	30	28	7
1.5m	0 m	1.87 m	4.0	79	74	70	66	69	65	62	58	51	48	46	43	34	32	31	8
2	0	2.39	5.0	81	77	73	70	71	68	65	62	53	50	48	46	35	34	32	9
2.5	0	2.95	7.0	83	80	77	74	73	71	68	66	55	53	51	49	37	36	34	10
3	0	3.52	10.0	85	83	80	78	75	73	71	69	56	55	53	52	38	37	36	11

