

# 屋内照明器具特性

品番 (品名)	S Q 4 4 0 A ( O P E N )									
光源	LED5000_70_350 x1					350.0 l m				
管理番号	K0160361 ( 0 ) DR 1									
B Z 分類	B Z 5 / 0 . 7 / B Z 4									

器具効率	97 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	4 %																			
下方光束	93 %																			
室指数	照明率 ( X 0 . 0 1 )																Z C M			
保守率	良 中 否	0.69	0.6	5.4	4.2	3.5	2.9	5.3	4.1	3.4	2.9	5.0	4.0	3.3	2.9	4.7	3.9	3.3	2.8	2.6
		0.67	0.8	6.6	5.5	4.8	4.2	6.4	5.4	4.7	4.2	6.1	5.2	4.6	4.1	5.8	5.1	4.5	4.1	3.8
		0.63	1.0	7.3	6.3	5.6	5.1	7.1	6.2	5.6	5.1	6.8	6.0	5.5	5.0	6.5	5.9	5.4	4.9	4.7
			1.25	7.9	7.1	6.4	5.9	7.8	7.0	6.4	5.9	7.4	6.8	6.2	5.8	7.1	6.6	6.1	5.7	5.5
下方投影面積		c m <sup>2</sup>																		
等価発光面積		c m <sup>2</sup>																		
取付高さ	器具間隔最大限																			
	横方向 ( A )	縦方向 ( B )																		
H m	1.12 H m	1.76 H m	3.0	9.4	8.9	8.6	8.2	9.2	8.8	8.4	8.1	8.9	8.5	8.2	8.0	8.6	8.3	8.0	7.8	7.5
			4.0	9.7	9.3	9.0	8.7	9.5	9.2	8.9	8.6	9.2	8.9	8.6	8.4	8.8	8.6	8.4	8.2	7.9
			5.0	9.8	9.5	9.3	9.0	9.6	9.4	9.1	8.9	9.3	9.1	8.9	8.7	9.0	8.8	8.7	8.5	8.1
			7.0	10.0	9.8	9.6	9.4	9.8	9.6	9.5	9.3	9.5	9.3	9.2	9.0	9.2	9.1	8.9	8.8	8.5
			10.0	10.1	10.0	9.8	9.7	10.0	9.8	9.7	9.6	9.6	9.5	9.4	9.3	9.3	9.2	9.2	9.1	8.7

