

屋内照明器具特性

品番 (品名)	S P L 5 4 2 6									
光源	LED2700_70_1805 ×1					1805.0 lm				
管理番号	K0142770(0)DB1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		12%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		88%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	0.6	53	41	33	28	52	40	33	27	48	38	31	26	45	36	30	26	23
	中	0.6	0.6	0.6	63	51	43	37	61	50	42	37	57	47	41	36	53	45	39	35	31
	否	0.56	0.56	0.56	69	58	50	44	67	57	49	44	63	54	47	42	58	51	45	41	37
					75	65	57	52	73	63	56	51	68	60	54	49	64	57	52	47	43
下方投影面積			cm ²	1.25	75	65	57	52	73	63	56	51	68	60	54	49	64	57	52	47	43
	等価発光面積		cm ²	1.5	80	70	63	57	77	68	62	56	72	65	59	54	67	61	56	52	48
取付高さ	器具間隔最大限			2.0	85	77	71	65	82	75	69	64	77	71	66	62	73	68	63	60	55
	H _m	横方向 (A)		縦方向 (B)	2.5	89	82	76	71	86	80	74	70	81	76	71	67	76	72	68	65
1.17H _m		1.18H _m		3.0	91	85	80	75	89	83	78	74	83	79	75	71	79	75	71	68	63
				4.0	95	90	85	81	92	87	83	80	87	83	80	77	82	79	76	73	68
				5.0	97	92	89	85	94	90	87	84	89	86	83	80	84	81	79	77	71
				7.0	99	96	93	90	96	93	91	88	91	89	87	85	87	85	83	81	75
				10.0	101	98	96	94	98	96	94	92	93	91	90	88	89	87	86	84	78

