

屋内照明器具特性	
品番 (品名)	XFL328SC
光源	LDL40S.N/14/26(2600A) ×2      2600.0 1m
管理番号	K0126408(0)DB1
BZ分類	BZ3

器具効率	67%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	2%	床	10%				10%				10%				10%				0%	
下方光束	65%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良 0.81 中 0.77 否 0.68	0.6	41	34	29	26	40	34	29	26	39	33	29	26	37	32	28	25	24	
		0.8	49	42	37	34	48	41	37	34	46	40	36	34	44	39	36	33	32	
		1.0	53	47	43	40	52	46	42	39	50	45	42	39	48	44	41	38	37	
		1.25	57	52	48	45	56	51	47	44	54	50	46	44	52	48	45	43	41	
下方投影面積	c m <sup>2</sup>	1.5	59	55	51	48	58	54	51	48	56	52	49	47	54	51	48	46	45	
		2.0	63	59	56	53	61	58	55	53	59	56	54	52	57	55	53	51	49	
取付高さ	器具間隔最大限		2.5	65	61	59	56	63	60	58	56	61	59	57	55	59	57	55	54	52
	横方向 (A)	縦方向 (B)	3.0	66	63	61	59	65	62	60	58	62	60	58	57	60	59	57	56	54
1.5m	2.39m	1.93m	4.0	67	65	63	62	66	64	63	61	64	62	61	60	62	61	59	58	56
2	3.17	2.4	5.0	68	67	65	64	67	66	64	63	65	64	62	61	63	62	61	60	58
2.5	3.95	2.88	7.0	70	68	67	66	68	67	66	65	66	65	64	63	64	63	63	62	59
3	4.71	3.37	10.0	70	69	68	68	69	68	68	67	67	66	66	65	65	64	64	63	61

