

屋内照明器具特性	
品番 (品名)	XFL828B
光源	LDL110S.N/54/65K(6500) x2 6500.0 1m
管理番号	K0129359(1)DB1
BZ分類	BZ5

器具効率	95%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	95%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	5.2	4.0	3.3	2.7	5.1	4.0	3.3	2.7	4.9	3.9	3.2	2.7	4.7	3.8	3.2	2.7	2.5
	中	0.77	0.8	6.2	5.0	4.3	3.7	6.0	5.0	4.2	3.7	5.8	4.8	4.2	3.7	5.5	4.7	4.1	3.7	3.4
	否	0.68	1.0	6.8	5.7	5.0	4.4	6.6	5.7	4.9	4.4	6.4	5.5	4.9	4.4	6.1	5.4	4.8	4.3	4.1
			1.25	7.4	6.4	5.7	5.1	7.2	6.3	5.6	5.1	6.9	6.1	5.5	5.1	6.6	6.0	5.4	5.0	4.8
下方投影面積		cm ²	1.5	7.8	6.9	6.2	5.7	7.6	6.8	6.2	5.6	7.3	6.6	6.1	5.6	7.0	6.4	5.9	5.5	5.3
等価発光面積		cm ²	2.0	8.3	7.6	7.0	6.5	8.2	7.5	6.9	6.5	7.9	7.3	6.8	6.4	7.6	7.1	6.7	6.3	6.1
取付高さ	器具間隔最大限		2.5	8.7	8.1	7.5	7.1	8.5	8.0	7.5	7.0	8.2	7.7	7.3	6.9	8.0	7.5	7.2	6.9	6.6
	横方向 (A)	縦方向 (B)	3.0	8.9	8.4	7.9	7.5	8.8	8.3	7.8	7.5	8.5	8.1	7.7	7.4	8.2	7.9	7.5	7.3	7.0
1.5m	2.13m	2.88m	4.0	9.3	8.8	8.4	8.1	9.1	8.7	8.4	8.0	8.8	8.5	8.2	7.9	8.6	8.3	8.0	7.8	7.5
2	2.78	3.31	5.0	9.5	9.1	8.8	8.5	9.3	9.0	8.7	8.4	9.0	8.8	8.5	8.3	8.8	8.6	8.3	8.1	7.9
2.5	3.43	3.81	7.0	9.7	9.4	9.2	8.9	9.5	9.3	9.1	8.9	9.3	9.1	8.9	8.7	9.0	8.9	8.7	8.6	8.3
3	4.08	4.34	10.0	9.8	9.7	9.5	9.3	9.7	9.5	9.4	9.2	9.5	9.3	9.2	9.0	9.2	9.1	9.0	8.9	8.6

